

FEATURES:

2 years warranty period
 MTBF – 300 000 h
 Meets energy star level V
 Universal AC input / full range



SPECIFICATION:

output	Model	Voltage DC [V]	Current min [A]	Current max/Peak max [A]	Tolerance [%]	Efficiency [%]	Power max/Peak max [W]	Ripple & noise [mV]	DC plug
	ESPE 6524	24	0	2,71 / 4*	+/- 5	>87	65 / 96	240	2,1x5,5x11
input	voltage	100 - 240V							
	voltage range	90 - 264V							
	frequency min. / max	47 - 63 Hz							
	frequency	60HZ / 50Hz							
	current	1,4 Amax @ 115VAC							
	inrush current	80 A max @ 230VAC							
	Over Voltage Protection (OVP)	(V outx150%) Max.							
	Short Circuit Protection (SCP)	Automatic recovery after short-circuit fault being removed							
	insulation	Class I							
	min. load requirement	No							
others	MTBF	300000h							
	efficiency	> 87 %							
	dimensions / weight	115 x 53 x 38 mm / 291g (50pcs/cartoon)							
environmental	operating temp.	0 ~40 deg C							
	storage temp.	-20 ~80 deg C							
	relative humidity	20 ~90% RH							
	storage relative humidity	10% ~90% RH							
safety	UL / cUL / GS/ PSE / BSMI / CB / RCM								
EMI	CE /FCC Class B; Conduction & Radiation Met.								

* 2.71A Max (Peak 4A/0.1 Sec Max,; It can provide continual use for 30 Sec.)