



Reversing starter, 3p, 0.55kW/400V/AC3, 100kA, +busbar adapter



Powering Business Worldwide™

Part no. MSC-R-1,6-
Article no. M7(230V50HZ)/BBA
Catalog No. 215641

Delivery programme

Basic function
 Basic function accessories

Busbar
 Busbar for miniature circuit-breaker
 Busbar for residual-current circuit-breakers
 Busbar for combined residual-current/power circuit-breaker
 2 phase
 EVG

Type
 Product range

Technical data ETIM 5.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)
 Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar
 (ecl@ss8-27-37-13-06 [ACN992007])

Number of phases		2
Suitable for number of devices		6
Pitch dimensions	mm	0
Cross section	mm ²	10
Length	mm	210
Rated permanent current I _u	A	63
Type of electric connection		Fork
Insulated		Yes
Rated surge voltage	kV	4
Conditioned rated short-circuit current I _q	kA	25
Max. rated operation voltage U _e	V	500
Rated short-time withstand current I _{cw}	kA	0
Suitable for devices with N-busbar		No
Suitable for devices with auxiliary switch		No