



**SPECIFICATION (WITH APPROVED PLUG)**  
 RATED: 10A / 20V 4.3uF  
 INSERTION FORCE: 2.5Kg max  
 WITHDRAWAL FORCE: 1.0Kg~2.5Kg  
 INSULATION RESISTANCE: >500MΩ@500VDC  
 WITHSTAND VOLTAGE: 250VAC/1 MIN  
 CONTACT RESISTANCE: <7mΩ

SUPPLIED TAPED + REELED 100x PER REEL

ISS.	AMEND	DATE
1	1st DRAWN	21/12/07
2	SPECN / PACKING ADD	15/01/07
3	Ø2.1 VARIANT DEL	21/11/12

<b>RoHS</b> COMPLIANT
<b>TOLERANCE</b> NO DEC. PLACE ±0.30 1 DEC. PLACE ±0.20 2 DEC. PLACE ±0.10 HOLE Ø ±0.10 ANGLES ± 1/2° UNLESS OTHERWISE STATED
DO NOT SCALE

**Cliff Electronic Components Ltd.**  
 76 Holmehorpe Avenue, Holmehorpe Industrial Estate,  
 Redhill, Surrey, RH1 2PF, England, UK  
 Tel: 01737-771375 Fax: 01737-766012 Website: www.cliffuk.co.uk

THE CONTENTS OF THIS DOCUMENT MUST NOT BE COPIED OR DISCLOSED TO A 3rd PARTY WITHOUT WRITTEN PERMISSION OF CLIFF UK. © 2007

DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE STATED. WORK TO DIMENSIONS. REMOVE ALL BURRS. IF IN DOUBT ASK.

MATERIAL: PPO / BRASS / SS / COPPER  
 FINISH: AS MOULDED / Sn / Ag PLATED  
 DRAWN: C.A.M.J.

PACKED ON TAPE / REEL  
 APPROVED: R.W.T.

3rd ANGLE PROJECTION:

TITLE: DC POWER SOCKET Ø2.5mm  
 DRWG. No. **FC681495**  
 FORM: A4DRWGH