



FIX-PE



MATERIAL: POLYETHYLENE  
 OPERATING TEMPERATURE: -10...40°C  
 MAX WORKING PRESSURE: 10bar  
 UNIT:mm

PART NO	Int. diam.	Out. diam.	Wall thickness	Length in roll[m]	Colour
FIX-PE-4/2-BK	2	4	1	30	black
FIX-PE-4/2-BL	2	4	1	30	blue
FIX-PE-4/2-N	2	4	1	30	natural
FIX-PE-4/2-RD	2	4	1	30	red
FIX-PE-5/3-BK	3	5	1	30	black
FIX-PE-5/3-BL	3	5	1	30	blue
FIX-PE-5/3-N	3	5	1	30	natural
FIX-PE-5/3-RD	3	5	1	30	red
FIX-PE-6/4-BK	4	6	1	30	black
FIX-PE-6/4-BL	4	6	1	30	blue
FIX-PE-6/4-N	4	6	1	30	natural
FIX-PE-6/4-RD	4	6	1	30	red
FIX-PE-8/5-BK	5	8	1,5	25	black
FIX-PE-8/5-BL	5	8	1,5	25	blue
FIX-PE-8/5-N	5	8	1,5	25	natural
FIX-PE-8/5-RD	5	8	1,5	25	red
FIX-PE-8/6-BK	6	8	1	25	black
FIX-PE-8/6-BL	6	8	1	25	blue
FIX-PE-8/6-N	6	8	1	25	natural
FIX-PE-8/6-RD	6	8	1	25	red
FIX-PE-10/8-BK	8	10	1	25	black

FIX-PE-10/8-BL	8	10	1	25	blue
FIX-PE-10/8-N	8	10	1	25	natural
FIX-PE-10/8-RD	8	10	1	25	red
FIX-PE-11/9-BK	9	1	1	25	black
FIX-PE-11/9-BL	9	1	1	25	blue
FIX-PE-11/9-N	9	1	1	25	natural
FIX-PE-11/9-RD	9	1	1	25	red
FIX-PE-12/10-BK	10	12	1	25	black
FIX-PE-12/10-BL	10	12	1	25	blue
FIX-PE-12/10-N	10	12	1	25	natural
FIX-PE-12/10-RD	10	12	1	25	red

**FIX**  
*Fasten*