



REVISIONS		
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 3. GOLD PL. 3 MIN THICK OVER NICKEL PL. 100 MIN THICK OVER COPPER STRIKE

1. CRIMPED FERRULE
 HEX CRIMP SIZE .128"
 2. CONTACT PIN TO SOLDER

DIMENSIONS ARE IN MILLIMETERS										PART NO. FME1121B4-ND3G-5-50		Amphenol		
UNLESS OTHERWISE SPECIFIED TOLERANCES										APPROVED				DATE
4	FERRULE	NOTE 1	NOTE 2	1	FR-39/32X95	0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4				DATE		TITLE		
3	CONTACT PIN	NOTE 1	NOTE 3	1	FME1121A4-4-15/06					10-11-01'		FME CRIMP PLUG (FOR RG-174/U,188A/U,316/U)		
2	INSULATOR	DELTRIN	NATURAL	1	FME1121B4-2-50					DATE		DRAWING NO.		
1	BODY	NOTE 1	NOTE 2	1	FME1121A4-1-27/17					10-11-01'		KJ-FME1121B4-ND3G-316U-50		
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	4/1	ISSUE	A	FILE NO.	ITEM NO.			