

# High-current probe

## HSS-118 305 065 A 2208

Item HSS-118-0570



GO TO PRODUCT

**ingun**<sup>®</sup>

Partner for Future Technology

### General data

Product group	High-current test probe
Sub-product group	Standard HSS (press-in)
Series	HSS-118
Grid	2.54 mm [100 mil]
Contacting from	Pad, Female connector
Magnetic	Yes
Installation type	Plug-in
Quick-exchange system	Yes
Adjustable installation height	No
Non-rotating	No
Compatible receptacle(s)	KS-112
Min. temperature	- 100 °C [- 212 °F]
Max. temperature	+ 200 °C [+ 392 °F]
RoHS-compliant	RoHS-3;6c

### Electrical data


Current load capacity / rated current	5 A
Typical resistance (Ri)	<10 mOhm

### Mechanical data



Total length	38.3 mm [1.50 in]
Barrel diameter	1.66 mm [.065 in]
Maximum stroke	8 mm [.314 in]
Spring pre-load	0.67 N [2.40 ozf]
Collar height	08
Spring force at working stroke	2.25 N [8.09 ozf]
Recommended working stroke	4 mm [.157 in]

### Tip style data

Tip style	05 bullet-nosed (full radius)
Tip diameter	0.65 mm [.025 in]
Tip style surface	A gold
Tip style material	3 CuBe



1:1




HIGH-CURRENT TEST PROBE

High-current probe  
**HSS-118 305 065 A 2208**  
Item HSS-118-0570



**ingun**<sup>®</sup>  
Partner for Future Technology



**INGUN Prüfmittelbau GmbH**

Max-Stromeyer-Straße 162  
78467, Constance, Germany  
Phone +49 7531 8105-0  
Customer hotline +49 7531 8105-888  
Fax +49 7531 8105-65  
info@ingun.com



Prices and delivery times on request.  
Technical changes reserved. 11/23 EN

Learn more about  
High-current test probe



HIGH-CURRENT TEST PROBE