

Inductive proximity switches are contact-free sensors. They detect all conductive metals, regardless of whether they move or not. The achievable sensing range of the devices depends on the object material and its dimensions. The vibration-resistant sensors can be approached laterally or frontally. Inductive proximity switches are used for presence detection (e.g. goods carriers), positioning (e.g. dampers), counting (e.g. nuts / bolts), speed detection (e.g. for cog wheels), on conveyor systems (e.g. hose feedings) or distance measurements (e.g. press-in checking) of metallic objects.


TECHNICAL DATA


Devices for hose mounting	NO
Feeding technology	NO
Hygienic and wet area	NO
Metallic sensor surface	NO
Oil and lubricating coolants	NO
Ring-shaped sensors	NO
Rough ambient conditions	NO
Welding proof sensors	NO
Ambient temperature (min/max)	-25°C / 70°C
Coating housing	Chromium-plated
Construction type housing	Cylinder, screw-thread
Degree of protection (IP)	IP67
High-pressure resistant sensors	NO
Increased ambient temperatures > 80°C	NO
Length of sensor	50mm
Material active area of sensor	PBTP
Material housing	Brass
Mechanical mounting condition for sensor	Quasi-flat
Pitch thread	1mm
Sensors unaffected by atmospheric changes (temperature cycle)	NO
Thread size metric (M..)	12
Absolute repeat accuracy	0.3mm
Correction factor (aluminium)	0.28
Correction factor (brass)	0.35
Correction factor (copper)	0.2
Correction factor (stainless steel)	0.47
Correction factor (steel)	1
Distance measuring sensors	YES
Increased sensing range	NO
Magnetic field resistant	NO
Measuring range length (min/max)	0mm / 6mm

inductive sensors (analog)

TECHNICAL DATA


No load current	12mA
Number of poles	4
Operating voltage (min/max)	15V / 30V
Reverse polarity protection	YES
Short-circuit-proof	YES
Standby delay	50ms
Supply voltage (min/max)	15V / 30V
Type of analogy output	0 V ... 10 V / 4 mA ... 20 mA
Type of electric connection	Cable
Voltage type	DC
Resolution	1µm

CONNECTION



Colors: BN (brown), WH (white), BU (blue), BK (black)
Functions: BN = L+, WH = 4-20mA, BU = L-, BK = 0-10V

DIMENSIONAL DRAWING



ADDITIONAL INFORMATION

