

Product data sheet

Specifications



Thorsman, Worklight 20W, IP65 Contour Plug 230V

IMT47225

Main

Range	Thorsman
Range of product	Thorsman Worklights
Product name	Worklight
Product or component type	Lamp
Device application	Mobile equipment Ware-houses and parking garages Hospital Residential Sports hall

Complementary

Type of installation	Outdoor
[Ue] rated operational voltage	230 V
Network type	AC
Operational power in W	20 W
Plug standard	Contour
Luminous flux	2000 lm
Bulb lifespan	50000 h
Colour rendering index	Ra=80
Colour temperature	4000 K
Beam angle	110 °
Power factor	0.7
Height	229.5 mm
Width	204.5 mm
Depth	40.0 mm
Net weight	850 g

Environment

Environmental characteristic	Water resistant Dust resistant UV resistant Impact resistant
IP degree of protection	IP65

IK degree of protection	IK05
Ambient air temperature for operation	-30...45 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23.5 cm
Package 1 Width	23.5 cm
Package 1 Length	23.5 cm
Package 1 Weight	900 g
Unit Type of Package 2	S03
Number of Units in Package 2	7
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	6.741 kg
Unit Type of Package 3	P12
Number of Units in Package 3	112
Package 3 Height	75 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	119.856 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)