Product data sheet Characteristics

MIP12112T

Enclosure, Resi9 MP, surface mounting, 1 row of 12 modules, IP40, translucid door, 1 earth + 1 neutral terminal blocks





Main

Range	Resi9	
Product name	Resi9 MP	
Product or component type	Enclosure	
Enclosure type	Modular enclosure	
Number of 18 mm modules per row	12	
Number of horizontal rows	1	
Type of front cover	Translucid	
Width	268 Mm outside:	
Height	228 Mm outside:	
Depth	101.5 Mm outside:	

Complementary

Enclosure mounting	Surface
9 mm pitches	24
Total number of 18 mm modules	12
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Mounting plate description	Without mounting plate
Cable entry	1 trunking flange 1 bare flange
Terminal block function	Earth / neutral
Number of terminal blocks	1 earth (screwed) with 8 outgoers 1 neutral (screwed) with 8 outgoers
Distribution block outgoers	1 x 16 mm² for earth 1 x 16 mm² for neutral 3 x 6 mm² for earth 3 x 6 mm² for neutral 4 x 10 mm² for earth 4 x 10 mm² for neutral
Enclosure material	Back part: technoplastic Door: technoplastic Front face: technoplastic
Internal depth	80 Mm
Colour	Front face: white (RAL 9003) Door: translucid
Market segment	Small commercial Residential

Environment

Standards	IEC 61439-1
	IEC 61439-3
	IEC 60670-1
	IEC 60670-24
Quality labels	IMQ
Fire resistance	Door: 650 °C
	Back part: 650 °C
	Front face: 650 °C
IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-2560 °C

Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.200 Cm
Package 1 Width	22.700 Cm
Package 1 Length	27.000 Cm
Package 1 Weight	804.000 G
Unit Type of Package 2	S04
Number of Units in Package 2	8
Package 2 Height	30.000 Cm
Package 2 Width	40.000 Cm
Package 2 Length	60.000 Cm
Package 2 Weight	7.309 Kg
Unit Type of Package 3	P12
Number of Units in Package 3	128
Package 3 Height	120.000 Cm
Package 3 Width	80.000 Cm
Package 3 Length	120.000 Cm
Package 3 Weight	128.944 Kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) [☑] EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : Commercialised

