Product data sheet Characteristics

MIP22118

Enclosure, Resi9 MP, flush mounting, 1 row of 18 modules, IP40, white door, 1 earth + 1 neutral terminal blocks





Main

Range	Resi9
Product name	Resi9 MP
Product or component type	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	18
Number of horizontal rows	1
Type of front cover	Plain
Width	378 Mm wall: 402 Mm outside:
Height	228 Mm wall: 252 Mm outside:
Depth	18 Mm outside: 80 Mm wall: 98 Mm total:

Complementary

Enclosure mounting	Flush	
9 mm pitches	36	
·		
Total number of 18 mm modules	18	
[In] rated current	63 A	
Type of rail	35 mm asymmetrical rail	
Mounting plate description	Without mounting plate	
Cable entry	Pre-cutted holes	
Terminal block function	Earth / neutral	
Number of terminal blocks	1 earth (screwed) with 16 outgoers	
	1 neutral (screwed) with 16 outgoers	
Distribution block outgoers	2 x 16 mm² for earth	
3	2 x 16 mm² for neutral	
	6 x 6 mm ² for earth	
	6 x 6 mm² for neutral	
	8 x 10 mm ² for earth	
	8 x 10 mm² for neutral	
Enclosure material	Back part: technoplastic	
	Door: technoplastic	
	Front face: technoplastic	
Internal depth	76 Mm	

Standards	IEC 61439-1
	IEC 61439-3
	IEC 60670-1
	IEC 60670-24
Quality labels	IMQ
Fire resistance	Door: 650 °C
	Back part: 650 °C
	Front face: 650 °C
IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-2560 °C

Packing Units

r doking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.900 Cm
Package 1 Width	40.200 Cm
Package 1 Length	25.200 Cm
Package 1 Weight	1.200 Kg
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	52.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	6.900 Kg
Unit Type of Package 3	P12
Number of Units in Package 3	80
Package 3 Height	120.000 Cm
Package 3 Width	80.000 Cm
Package 3 Length	120.000 Cm
Package 3 Weight	97.600 Kg

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) [™] EU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	[☑] China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Halogen content performance	Halogen free product	

Contractual warranty

Warranty	18 months

Product Life Status :	Commercialised	

