Product data sheet Characteristics

MIP22212T

Enclosure, Resi9 MP, flush mounting, 2 rows of 12 modules, IP40, translucid door, 1 earth + 1 neutral terminal blocks





Main

Range	Resi9	
Product name	Resi9 MP	
Product or component type	Enclosure	
Enclosure type	Modular enclosure	
Number of 18 mm modules per row	12	
Number of horizontal rows	2	
Type of front cover	Translucid	
Width	270 Mm wall: 294 Mm outside:	
Height	353 Mm wall: 377 Mm outside:	
Depth	18 Mm outside: 80 Mm wall: 98 Mm total:	

Complementary

Complementary		
Enclosure mounting	Flush	
9 mm pitches	24	
Total number of 18 mm modules	24	
[In] rated current	63 A	
Type of rail	35 mm asymmetrical rail	
Mounting plate description	Without mounting plate	
Cable entry	Pre-cutted holes	
Terminal block function	Earth / neutral	
Number of terminal blocks	1 earth (screwed) with 16 outgoers 1 neutral (screwed) with 16 outgoers	
Distribution block outgoers	2 x 16 mm² for earth 2 x 16 mm² for neutral 6 x 6 mm² for earth 6 x 6 mm² for neutral 8 x 10 mm² for earth 8 x 10 mm² for neutral	
Enclosure material	Back part: technoplastic Door: technoplastic Front face: technoplastic	
Internal depth	76 Mm	

Colour	Front face: white (RAL 9003) Door: translucid	
Market segment	Residential	
•	Small commercial	

Environment

Standards	IEC 61439-1
	IEC 61439-3
	IEC 60670-1
	IEC 60670-24
Quality labels	IMQ
Fire resistance	Door: 650 °C
	Back part: 650 °C
	Front face: 650 °C
IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-2560 °C

Packing Units

i acking critis	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.800 Cm
Package 1 Width	29.400 Cm
Package 1 Length	37.700 Cm
Package 1 Weight	1.280 Kg
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	52.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	8.050 Kg
Unit Type of Package 3	P12
Number of Units in Package 3	80
Package 3 Height	120.000 Cm
Package 3 Width	80.000 Cm
Package 3 Length	120.000 Cm
Package 3 Weight	116.000 Kg

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) [™] EU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	[™] China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Halogen content performance	Halogen free product	

Contractual warranty

Warranty	18 months

Product Life Status:	Commercialised	

