



Main

Range	Thalassa
Product name	Thalassa PLA
Device application	Multi-purpose
Product or component type	Suitable enclosure
Device short name	PLA
Enclosure nominal height	750 Mm
Enclosure nominal width	500 Mm
Enclosure nominal depth	420 Mm
Enclosure mounting	Floor-standing
Device composition	1 top part 1 bottom part 2 side part 1 rear panel 1 door

Complementary

Body type	Sealed top and bottom part assembled with side parts
Door type	Transparent front
Number of doors	1 door(s)
Door opening side	Reversible (120 °)
Lock type	2 points lock, 5 mm double-bar
Accessibility for operation	Front Rear
Removable parts	Door by hinges Rear panel by fixing element
Material	Polyester reinforced with fibreglass
Colour	Grey (RAL 7035)
Standards	IEC 62208 UL 508 A
NEMA degree of protection	NEMA 5 NEMA 3 NEMA 12 NEMA 3X NEMA 3R NEMA 1 NEMA 2 NEMA 13 NEMA 3S

Product certifications	DNV Marine Veritas UL/CUL listed
Electrical insulation class	Class II

Environment

IP degree of protection	IP65 conforming to IEC 60529 (completely sealed)
IK degree of protection	IK08 conforming to IEC 62262 (glazed door)
Fire resistance	960 °C conforming to IEC 62208
Ambient air temperature for storage	-35...90 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	76.0 Cm
Package 1 Width	54.0 Cm
Package 1 Length	48.0 Cm
Package 1 Weight	20.39 Kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Product Life Status : **Commercialised**