



## Main

|                           |  |
|---------------------------|--|
| Range                     | Thalassa   |
| Product name              | Thalassa PLA   |
| Device application        | Multi-purpose  |
| Product or component type | Suitable enclosure   |
| Device short name         | PLAT   |
| Enclosure nominal height  | 750 Mm   |
| Enclosure nominal width   | 500 Mm   |
| Enclosure nominal depth   | 320 Mm   |
| Enclosure mounting        | Floor-standing   |
| Device composition        | 1 top part<br>1 bottom part<br>2 side part<br>1 rear panel<br>1 door<br>1 canopy |

## Complementary

|                             |  |
|-----------------------------|--|
| Body type                   | Open top and sealed bottom part assembled with side parts                  |
| Door type                   | Plain front  |
| Number of doors             | 1 door(s)  |
| Door opening side           | Reversible (120 °)   |
| Lock type                   | 2 points handle lock, 5 mm double-bar                                      |
| Accessibility for operation | Top<br>Rear<br>Front   |
| Removable parts             | Door by hinges<br>Rear panel by fixing element<br>Canopy by fixing element |
| Material                    | Polyester reinforced with fibreglass                                       |
| Colour                      | Grey (RAL 7035)  |
| Standards                   | IEC 62208  |
| Product certifications      | Veritas  |
| Electrical insulation class | Class II   |

## Environment

|                                     |   |
|-------------------------------------|---|
| IP degree of protection             | IP44 conforming to IEC 60529 (with ventilated canopy) |
| IK degree of protection             | IK10 conforming to IEC 62262 (plain door)             |
| Fire resistance                     | 960 °C conforming to IEC 62208                        |
| Ambient air temperature for storage | -35...90 °C   |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 38.0 Cm  |
| Package 1 Width              | 53.5 Cm  |
| Package 1 Length             | 77.0 Cm  |
| Package 1 Weight             | 18.79 Kg |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product  |
| REACH Regulation           | <a href="#">REACH Declaration</a>  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes  |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>   |
| RoHS exemption information | <a href="#">Yes</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>  |

Product Life Status : **Commercialised**