Product data sheet Characteristics

NSYPLAZ573G

Floor standing polyester enclosure, Thalassa PLA, plain door, open bottom, 500x750x320mm, IP54, IK10





Main

Range	Thalassa	
Product name	Thalassa PLA	
Device application	Multi-purpose	
Product or component type	Suitable enclosure	
Device short name	PLAZ	
Enclosure nominal height	500 Mm	
Enclosure nominal width	750 Mm	
Enclosure nominal depth	320 Mm	
Enclosure mounting	Floor-standing	
Device composition	1 top part 1 bottom part 2 side part 1 rear panel 1 door 1 plinth	

Complementary

Body type	Sealed top and open bottom part assembled with side parts	
Door type	Plain front	
Number of doors	1 door(s)	
Door opening side	Reversible (120 °)	
Lock type	2 points handle lock, 5 mm double-bar	
Accessibility for operation	Front Rear Bottom	
Removable parts	Door by hinges Rear panel by fixing element	
Material	Polyester reinforced with fibreglass	
Colour	Grey (RAL 7035)	
Standards	IEC 62208	
Product certifications	Veritas	
Electrical insulation class	Class II	

Environment

P degree of protection IP54 conforming to IEC 60529 (plinth type open bottom)		
IK degree of protection	ection IK10 conforming to IEC 62262 (plain door)	
Fire resistance 960 °C conforming to IEC 62208		
Ambient air temperature for storage	-3590 °C	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	56.0 Cm
Package 1 Width	78.0 Cm
Package 1 Length	38.0 Cm
Package 1 Weight	20.082 Kg

Offer Sustainability

Office Oddital lability		
Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV EU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	

Product Life Status:	Commercialised	
----------------------	----------------	--