# Product data sheet Characteristics

## **NSYS3D6830**

Wall mounted steel enclosure, Spacial S3D, plain door, without mounting plate, 600x800x300mm, IP66, IK10





#### Main

Spacial	
Spacial S3D	
Multi-purpose	
Compact enclosure	
600 Mm	
800 Mm	
300 Mm	
Plain	
Without mounting plate	
Standard	
Wall-mounting	
1 body	
· ·	
1 door	
1 lock	
	Spacial S3D  Multi-purpose  Compact enclosure  600 Mm  800 Mm  300 Mm  Plain  Without mounting plate  Standard  Wall-mounting  1 body 2 cable gland plate 1 door

#### Complementary

Variant particularity	Single piece body	
	Gutter-shaped front rail double sheet thickness	
Number of doors	Front face: 1 door(s)	
Door opening side	Reversible (120 °)	
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	Front	
Removable parts	Door by hinges	
	Cable gland plate by screws	
Material	Steel	
Surface finish	Epoxy-polyester powder	
Colour	Grey (RAL 7035)	
Standards	IEC 62208	
Product certifications	LR	
	CUL	
	DNV	
	GL	
	BV	
	UL	
Product weight	25.5 Kg	

#### Environment

NEMA degree of protection	NEMA 4X/13	
IK degree of protection	IK10 conforming to IEC 62262	
IP degree of protection	IP66 conforming to IEC 60529	

### Packing Units

· coming or mo	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	35 Cm
Package 1 Width	62 Cm
Package 1 Length	81.5 Cm
Package 1 Weight	21.8 Kg
Unit Type of Package 2	PAM
Number of Units in Package 2	8
Package 2 Height	177.5 Cm
Package 2 Width	100 Cm
Package 2 Length	120 Cm
Package 2 Weight	204 Kg

#### Offer Sustainability

Green Premium product
☑ REACh Declaration
Pro-active compliance (Product out of EU RoHS legal scope) <sup>☑</sup> EU RoHS Declaration
Yes
☑ China RoHS Declaration
₫Yes
Product Environmental Profile

## Contractual warranty

Product Life Status : Commercialised