# Product data sheet Characteristics

## NSYS3D8625T

Wall mounted steel enclosure, Spacial S3D, transparent door, without mounting plate, 800x600x250mm, IP66, IK08





#### Main

Spacial	
Spacial S3D	
Multi-purpose	
Compact enclosure	
800 Mm	
600 Mm	
250 Mm	
Glazed	
Without mounting plate	
Standard	
Wall-mounting	
1 body	
1 door	
1 lock	
1 cable gland plate	
	Spacial S3D  Multi-purpose  Compact enclosure  800 Mm  600 Mm  250 Mm  Glazed  Without mounting plate  Standard  Wall-mounting  1 body 1 door 1 lock

#### Complementary

Complementary		
Variant particularity	Single piece body Gutter-shaped front rail double sheet thickness	
Number of doors	Front face: 1 door(s)	
Door opening side	Reversible (120 °)	
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	Front	
Removable parts	Door by hinges Cable gland plate by screws	
Material	Body: steel Door: steel and security glass	
Surface finish	Epoxy-polyester powder	
Colour	Grey (RAL 7035)	
Standards	IEC 62208	
Product certifications	DNV GL LR CUL UL BV	
Product weight	22 Kg	

#### Environment

Electromagnetic compatibility	Electromagnetic field immunity test
NEMA degree of protection	NEMA 4X/13
IK degree of protection	IK08 conforming to IEC 62262
IP degree of protection	IP66 conforming to IEC 60529

## Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	81.3 Cm	
Package 1 Width	61.8 Cm	
Package 1 Length	29.8 Cm	
Package 1 Weight	22.0 Kg	

#### Offer Sustainability

Onor Guotamabinty	
Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₽¥Yes
Environmental Disclosure	Product Environmental Profile

## Contractual warranty

Product Life Status :
-----------------------