# Product data sheet Characteristics

# NSYS3D8630T

Wall mounted steel enclosure, Spacial S3D, transparent door, without mounting plate, 800x600x300mm, IP66, IK08





#### Main

Wall		
Range	Spacial	
Product name	Spacial S3D	
Device application	Multi-purpose	
Product or component type	Compact enclosure	
Enclosure nominal height	800 Mm	
Enclosure nominal width	600 Mm	
Enclosure nominal depth	300 Mm	
Door type	Glazed	
Mounting plate description	Without mounting plate	
Type of gland plate	Standard	
Installation accessory type	Wall-mounting	
Device composition	1 body	
	1 door	
	1 lock	
	1 cable gland plate	

## Complementary

Variant particularity	Gutter-shaped front rail double sheet thickness Single piece body	
Number of doors	Front face: 1 door(s)	
Door opening side	Reversible (120 °)	
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	Front	
Removable parts	Door by hinges Cable gland plate by screws	
Material	Body: steel Door: steel and security glass	
Surface finish	Epoxy-polyester powder	
Colour	Grey (RAL 7035)	
Standards	IEC 62208	
Product certifications	LR UL BV CUL GL DNV	
Product weight	24 Kg	

#### **Environment**

Electromagnetic compatibility	Electromagnetic field immunity test
NEMA degree of protection	NEMA 4X/13
IK degree of protection	IK08 conforming to IEC 62262
IP degree of protection	IP66 conforming to IEC 60529

# Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	34.5 Cm
Package 1 Width	61.5 Cm
Package 1 Length	81.5 Cm
Package 1 Weight	21.2 Kg
Unit Type of Package 2	PAM
Number of Units in Package 2	8
Package 2 Height	177.5 Cm
Package 2 Width	100.0 Cm
Package 2 Length	120.0 Cm
Package 2 Weight	183.0 Kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile

### Contractual warranty

Warranty	18 months	

Product Life Status : Commercialised