Product data sheet Characteristics

NSYS3X302515H

Wall mounted enclosure, Spacial S3X, stainless steel 316L, plain door, 300x250x150mm, IP66





Main

Range	Spacial	
Product name	Spacial S3X	
Device application	Multi-purpose	
Product or component type	Compact enclosure	
Enclosure nominal height	300 Mm	
Enclosure nominal width	250 Mm	
Enclosure nominal depth	150 Mm	
Installation accessory type	Wall-mounting	
Device composition	1 body 1 lock: door 1 door	

Complementary

Body type	Single piece body, cross-shaped structure Gutter shaped front rail	
Door type	Plain	
Number of doors	Front face: 1 door(s)	
Door opening side	Reversible (120 °)	
Lock type	3 mm double-bar lock	
Mounting plate description	Without mounting plate	
Type of gland plate	Without gland plate	
Accessibility for operation	Front	
Removable parts	Door by hinges	
Material	Lock: zamak Hinge: stainless steel Body and door: stainless steel 316L	
Surface finish	Body and door: Scotch-Brite® brushed Lock: chromium plated	
Product weight	3.574 Kg	

Environment

Standards	IEC 62208	
Product certifications	CAN/CSA 22 UL 508 type A	
IP degree of protection	IP66 conforming to IEC 60529	
IK degree of protection	IK10 conforming to IEC 62262	
Environmental characteristic	Specific hygiene Corrosive	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	31.75 Cm
Package 1 Width	17.526 Cm
Package 1 Length	25.908 Cm
Package 1 Weight	3.465 Kg
Unit Type of Package 2	PAM
Number of Units in Package 2	135
Package 2 Height	195 Cm
Package 2 Width	100 Cm
Package 2 Length	120 Cm
Package 2 Weight	495 Kg

Offer Sustainability

	sustainable offer status	
	REACh Regulation	
cope) EU RoHS Decla-	EU RoHS Directive Pro-active compliance (Product out of EU Rohration	
	Mercury free	
	china RoHS Regulation	
	OHS exemption information	
	invironmental Disclosure	
	nvironmental Disclosure	

Contractual warranty

Warranty	18 months

Product Life Status : Commercialised