Product data sheet Characteristics

NSYS3X3215

Wall mounted enclosure, Spacial S3X, stainless steel 304L, plain door, 300x200x150mm, IP66





Main

Range	Spacial	
Product name	Spacial S3X	
Device application	Multi-purpose	
Product or component type	Compact enclosure	
Enclosure nominal height	300 Mm	
Enclosure nominal width	200 Mm	
Enclosure nominal depth	150 Mm	
Installation accessory type	Wall-mounting	
Device composition	1 body 1 lock: door 1 door	

Complementary

Body type	Single piece body, cross-shaped structure Gutter shaped front rail	
Door type	Plain	
Number of doors	Front face: 1 door(s)	
Door opening side	Reversible (120 °)	
Lock type	3 mm double-bar lock	
Mounting plate description	Without mounting plate	
Type of gland plate	Without gland plate	
Accessibility for operation	Front	
Removable parts	Door by hinges	
Material	Body and door: stainless steel 304L Lock: zamak Hinge: stainless steel	
Surface finish	Body and door: Scotch-Brite® brushed Lock: chromium plated	
Product weight	3.08 Kg	

Environment

Standards	IEC 62208	
Product certifications	UL 508 type A CAN/CSA 22	
IP degree of protection	IP66 conforming to IEC 60529	
IK degree of protection	IK10 conforming to IEC 62262	
Environmental characteristic	Corrosive Specific hygiene	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	16.5 Cm	
Package 1 Width	21.0 Cm	
Package 1 Length	31.0 Cm	
Package 1 Weight	2.95 Kg	

Offer Sustainability

Green Premium product
☑ REACh Declaration
Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Yes
☑ China RoHS Declaration
₫Yes
Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status: Commercialised