Product data sheet Characteristics

NSYTBS885

ABS box IP66 IK07 RAL7035 Int.H80W80D65 Ext.H89W89D51 Opaque cover H10



Main Range Thalassa TBS Device application Multi-purpose Category Industrial box Height 89 mm Width 89 mm 54 mm Depth Internal height 80 mm Internal width 80 mm Internal depth 47 mm Enclosure mounting Wall mounted Device composition 4 x cover screw 1 x cover 1 x body Set of 5 Quantity per set Body type One piece moulded Type of front cover Low plain cover Cover fixing Metal screws Lock type Outside sealed area: flat screwdriver captive screw

Cover, by captive screws

Complementary

Complementary		
Material	ABS	
Colour	Grey (RAL 7035)	
Standards	IEC 62208	
Product certifications	DEMKO SEMKO TÜV	
IP degree of protection	IP66conforming to NEMA 4.4X	
IK degree of protection	IK07conforming to IEC 62262	
Fire resistance	650 °C conforming to IEC 60695-2-11	
Ambient air temperature for storage	-1540 °C	
Operating temperature	-2560 °C	

Removable parts

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations