Technical data sheet

UDHOME4 floor box, with universal support UT3, triple NF.

Item no. 7427208





Square floor box for use in dry-cleaned cavity and screed floors for indoor use. Installation housing with pre-marked insertion openings for pipelines (M25). Cover adjustable to top edge of floor covering using four height-adjustment supports. 15 mm floor covering recess in the hinged cover. The minimum installation depth is 95 mm, the height-adjustment range \pm 30 mm.

The scope of delivery contains two UT3 universal supports, a triple NF socket with cover plate and two individual cover plates for accessories with support ring.

Surfaces visible in the floor covering made of: Stainless steel, material 1.4301.


VA


Stainless steel, rustproof 1.4301

Master data

Item no.	7427208
Туре	UDHOME4 2V N
Description 1	Floor box, complete
Description 2	triple NF socket
Material	Stainless steel, material no. 1.4301
Material symbol	A2
Smallest sales unit (VG)	1 Piece
Weight	414,00 kg/100 pc.

Technical data





Length	199,00 mm
Width	199,00 mm
Dimension h	95,00 mm
Wide external dimensions	199,00 mm
Wide installation dimensions	205,00 mm
Length of external dimensions	199,00 mm
Length of installation dimensions	205,00 mm
Number of mounting boxes	2
Cable outlet version	Swivellable cord outlet
Floor covering thickness	15,00 mm
Floor covering protection frame	
Version for	Square
Screed height	95-110 mm
Floor height	95-125 mm
Suitable for wet care	
Suitable for raised floor installation	
Suitable for cavity floor installation	
Suitable for underfloor ducts	
With floor covering recess	
Height-adjustment range	95,00 - 125,00 mm
Opening mechanism	Handle