

## LED light bar OPBxx5630-02924WL

# LED light bar OPBxx5630-02924WL - PRODUCT DATASHEET



Voltage	24 V DC
Power	11,0 W/m
Luminocity	1320 lm/m
Qty LED	29 LED/m
Distance between LED	34,2 mm
Can be cut into section	24 cm

#### Powered by



#### **Basic information:**

• PL LINE PRODUCT- PROFESSIONAL LINE, HIGHEST QUALITY, LUMINOSITY AND DURABILITY

- PROFESSIONAL PCB MOUNTING, ONLY BRAND-NAME LED DIODES (LITEON)
- MODULES CAN BE SPLIT INTO 24 CM SECTIONS (7LED)
- MODULES CAN BE JOINED INTO LONGER STRINGS (MAXIMUM LENGHT OF LED SECTION WITH ONE POWER-SUPPLY POINT: 5M)

#### **Typical application:**

- UTILITY, DECORATIVE LIGHTING
- CEILING, WALL, NICHE, SHELF, PASSAGEWAYS BACKLIGHTING
- ADVERTISING (SIGNBOARDS): SHOP, MUSEUM, TARDE FAIRS EXPOSITIONS ETC. • KITCHEN WORKTOPS LIGHTING

#### **Explanation:**

• "xx" - COLOR DESIGNATION E.G. WH, WN AND WW





### **Additional Information**

Color	Cool white WH	Cool white WH	Warm white WW	Warm white WW	Neutral white WN	Warm white WW
Voltage	24 V DC					
Power	8,0 W/m					
Power of single LED	0,27 W					
Current		0,33 A/m				
Luminocity	1320 lm/m	1320 lm/m	1280 lm/m	1280 lm/m	1320 lm/m	1150 lm/m
Qty LED	29 LED/m					
Distance between LED	34,2 mm					
Can be cut into section	24 cm					
Width	10 mm					
Height	3 mm					
Color temperature / Wavelenght scope	6500 K	5000 K	3500 K	3000 K	4000 K	2700 K
Beam angle	120°					
Color rendering index (Ra)	80					
Operating temperature	-25 - +60°C					
Storage temperature	-40 - +80°C					
IP degree			IP	20		
		240,00			~	
e	1	-240,00				
				• 8		

In spite of all our efforts, we do not guarantee, that technical data doesn't include any mistakes or defects, which can't be basis of any claiming. Figures and pictures are for illustration only and can be different from authentic appearance of product.