




Material	Polyamid
O-Ring	NBR
Schutzart	IP 54 bei starrer Schlauchmontage IP 65
Dauergebrauchstemperatur	-20 °C – +80 °C
Lieferfarbe	schwarz (RAL 9005)



// Schutz gegen unbeabsichtigtes Öffnen, kann nur mit Schraubendreher demontiert werden



AG	D mm	GL mm	H mm	L mm	Ø mm	passend zu Polyamid-Schlauch DN	Best.-Nr.
M 16 x 1,5	20	8	23	43	19	10	1.513.1601.50
M 20 x 1,5	26,5	9	30,5	52	24	14	1.513.2001.50
M 25 x 1,5	38,5	11	40	70	33	23	1.513.2501.50
M 32 x 1,5	46	11	51,5	83	42	29	1.513.3201.50
PG 9	19	8	23	43	19	10	1.513.0901.14
PG 11	23	8	27	48	22	12	1.513.1101.14
PG 13,5	26,5	9	30,5	52	24	14	1.513.1301.14
PG 16	30	10	32,5	56	27	17	1.513.1601.14
PG 21	38,5	11	40	70	33	23	1.513.2101.14
PG 29	46	11	51,5	83	42	29	1.513.2901.14
NPT 3/8"	19	15	23	43	19	10	1.513.3801.70
NPT 1/2"	30	13	32,5	56	27	17	1.513.1217.70
NPT 3/4"	38,5	13	40	70	33	23	1.513.3401.70
NPT 1"	46	15	51,5	83	42	29	1.513.1001.70