FIBOX
Enclosing innovations

MNX PC 100/75 HT

Sample photo

Order symbol:	PC 100/75 HT	**EAN:**	6418074024428
Product nbr:	6011902	**El. number:**	
Description:	Enclosure, PC	Finland:	3422253
Remarks:	Smoked transparent cover	Denmark:	8212022580
		Italy:	7352027
		Sweden:	2535613
		Norway:	

Including: Base with TPE gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

Dimensions:	**Length**	**Width**	**Height**
mm:	130	80	75
inch:	5.1	3.1	3.0

Materials:	
Material:	Polycarbonate
Base colour:	RAL 7035
Cover colour:	Smoked grey
Cover screws material:	Polyamide
Cover screws colour:	Black
Gasket material:	TPE

Temperatures:	
Short term:	-40 … 120 °C
Continuous:	-40 … 80 °C
Short term:	-40 … 250 °F
Continuous:	-40 … 175 °F

Accessories:	
MIV 100	Mounting plate (Galvanized steel)
MIN 5	DIN-15 Mounting rail
MIN 10	DIN-15 Mounting rail
MIV 5	DIN-35 Mounting rail
MIV 10	DIN-35 Mounting rail
FP A 100/130	Front plate (Aluminium)
HFP 130	Front plate hinge series
FP 22046	Wall fastening lug (4 pcs)

Rating:

Ingress Protection (EN 60529): IP 66/67
Impact Resistance (EN 62262): IK 08
Electrical insulation: Totally insulated
Halogen free (DIN/VDE 0472, Part 815): Yes
UV resistance: UL 508
Flammability Rating (UL 746 C 5): UL 746C 5V
Glow Wire Test (IEC 695-2-1) °C: 960
NEMA Class: NEMA 1, 4, 4X, 6

Certificates:

Germanischer Lloyd (GL)
Det Norske Veritas
Fimko
Europe EN 62208: 2003
Gost R



© Fibox Oy, Data subject to change without notice (printed: 28.4.2014)