

**MNX PC 200/88 XHG**



Sample photo

**Order symbol:** PC 200/88 XHG  
**Product nbr:** 6013330  
**Description:** Enclosure, PC  
**Remarks:** Grey cover

**EAN:** 6418074051936  
**EI. number:**  
 Finland: 3435262  
 Electric No. 8212022878  
 Denmark:  
 Electric No. Sweden: 6013330

Including: Base with PUR gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

| Dimensions:                         |                                   |       |        | Accessories:                             |                            |
|-------------------------------------|-----------------------------------|-------|--------|------------------------------------------|----------------------------|
|                                     | Length                            | Width | Height |                                          |                            |
| <b>mm:</b>                          | 255                               | 180   | 88     | MIN 15                                   | DIN-15 Mounting rail       |
| <b>inch:</b>                        | 10.0                              | 7.1   | 3.5    | MIN 20                                   | DIN-15 Mounting rail       |
| <b>Materials:</b>                   |                                   |       |        | MIV 15                                   | DIN-35 Mounting rail       |
| <b>Material:</b>                    | Polycarbonate                     |       |        | MIV 20                                   | DIN-35 Mounting rail       |
| <b>Base colour:</b>                 | RAL 7035 -light grey              |       |        | FP A 200/180                             | Front plate (Aluminium)    |
| <b>Cover screws material:</b>       | Polyamide                         |       |        | HFP 180                                  | Front plate hinge series   |
| <b>Cover colour:</b>                | RAL 7035 -light grey              |       |        | FP 22046                                 | Wall fastening lug (4 pcs) |
| <b>Cover screws colour:</b>         | Grey                              |       |        | <b>Rating:</b>                           |                            |
| <b>Gasket material:</b>             | Polyurethane                      |       |        | Ingress Protection (EN 60529): IP66/IP67 |                            |
| <b>Temperatures:</b>                |                                   |       |        | Impact Resistance (EN 62262): IK08       |                            |
| <b>Temperature °C (short term):</b> | -40 ... 120 °C                    |       |        | Electrical insulation: Totally insulated |                            |
| <b>Temperature °C (continuous):</b> | -40 ... 80 °C                     |       |        | Halogen free (DIN/VDE 0472, Part 815): 1 |                            |
| <b>Temperature °F (short term):</b> | -40 ... 250 °F                    |       |        | UV resistance: UL 508                    |                            |
| <b>Temperature °F (continuous):</b> | -40 ... 175 °F                    |       |        | Flammability Rating: UL 746C 5"          |                            |
| <b>Accessories:</b>                 |                                   |       |        | Glow Wire Test (IEC 695-2-1) °C: 960     |                            |
| MIV 200                             | Mounting plate (Galvanized steel) |       |        | NEMA Class: NEMA 1, 4, 4X, 6, 12, 13     |                            |
|                                     |                                   |       |        | <b>Certificates:</b>                     |                            |
|                                     |                                   |       |        | Germanischer Lloyd (GL)                  |                            |
|                                     |                                   |       |        | SGS Fimko                                |                            |
|                                     |                                   |       |        | Gost R                                   |                            |

