

SPECIFICATIONS


CUSTOMER	:	
SAMPLE CODE	:	SH800480T037-ZAA
MASS PRODUCTION CODE	:	PH800480T037-ZAA
SAMPLE VERSION	:	01
SPECIFICATIONS EDITION	:	001
DRAWING NO. (Ver.)	:	LMD-PH800480T037-ZAA (Ver.001)
PACKAGING NO. (Ver.)	:	-

Customer Approved

Date:

Approved	Checked	Designer
廖志豪 Rex Liao	張慶源 Yuan Chang	陳宗淇 Howard Chen

- ☒ Preliminary specification for design input
☐ Specification for sample approval



POWERTIP TECH. CORP.

Headquarters: No.8, 6th Road, Taichung Industrial Park,
Taichung, Taiwan
台中市 407 工業區六路 8 號

TEL: 886-4-2355-8168
FAX: 886-4-2355-8166

E-mail: sales@powertip.com.tw
[Http://www.powertip.com.tw](http://www.powertip.com.tw)

NO.PT-A-005-8

History of Version

<u>Date</u> (mm / dd / yyyy)	<u>Ver.</u>	<u>Edi.</u>	<u>Description</u>	<u>Page</u>	<u>Design by</u>
12/13/2023	01	001	Preliminary.	-	Howard

Contents

1. SPECIFICATIONS

- 1.1 Features
- 1.2 Mechanical Specifications
- 1.3 Absolute Maximum Ratings
- 1.4 DC Electrical Characteristics
- 1.5 Optical Characteristics
- 1.6 Backlight Characteristics

2. MODULE STRUCTURE

- 2.1 Counter Drawing
- 2.2 Interface Pin Description
- 2.3 Timing Characteristics

3. QUALITY ASSURANCE SYSTEM

- 3.1 Quality Assurance Flow Chart
- 3.2 Inspection Specification

4. RELIABILITY TEST

- 4.1 Reliability Test Condition

5. PRECAUTION RELATING PRODUCT HANDLING

- 5.1 Safety
- 5.2 Handling
- 5.3 Storage
- 5.4 Terms of Warranty

Appendix:

- 1.LCM Drawing

1. SPECIFICATIONS

1.1 Features

<u>Item</u>	<u>Standard Value</u>
Display Resolution	800 * 3 (RGB) * 480 Dots
LCD Type	Full Viewing Angle, Normally Black , Transmissive type
Screen size(inch)	7.0 inch
Color configuration	RGB Vertical Strip
Backlight Type	White LED B/L
Weight	-g
Interface	RGB interface
Other(controller/driver IC)	ST72568 (Or Compatible IC)
ROHS	THIS PRODUCT CONFORMS THE ROHS OF PTC Detail information please refer website : http://www.powertip.com.tw/news_detail.php?Key=1&cID=1

1.2 Mechanical Specifications

<u>Item</u>	<u>Standard Value</u>	<u>Unit</u>
Outline Dimension	164.9(W) x 100.0(L) x 3.4(H)	mm

LCD panel

<u>Item</u>	<u>Standard Value</u>	<u>Unit</u>
Active Area	153.84 (W) x 85.632(L)	mm
Pixel Size	0.1923(W) * 0.1784(H)	mm

Note: For detailed information please refer to LCM drawing

1.3 Absolute Maximum Ratings

Module

<u>Item</u>	<u>Symbol</u>	<u>Condition</u>	<u>Min.</u>	<u>Max.</u>	<u>Unit</u>	<u>Remark</u>
Power Supply for TFT Panel	DVDD	GND=0	-0.3	4.0	V	-
Operating Temperature	T _{OP} (Ts)	Note 1	-20	+70	°C	
Storage Temperature	T _{ST} (Ta)	Note 2	-30	+80	°C	

The absolute maximum rating values of this product are not allowed to be exceeded at any time. Should a module be used with any of the absolute maximum ratings exceeded, the characteristics of the module may not be recovered, or in an extreme case, the module may be permanently destroyed.

Note 1: Ts is the temperature of panel's surface

Note 2: Ta is the ambient temperature of samples

1.4 DC Electrical Characteristics

Module

GND = 0V, Ta = 25°C

<u>Item</u>	<u>Symbol</u>	<u>Condition</u>	<u>Min.</u>	<u>Typ.</u>	<u>Max.</u>	<u>Unit</u>
Power Supply for TFT Panel	DVDD	GND=0V	3.1	3.3	3.6	V
Input Voltage for TFT Panel	V _{IH}	GND=0V	0.7DVDD	-	DVDD	V
	V _{IL}	GND=0V	0	-	0.3DVDD	
Supply Current for TFT Panel	DIDD	DIDD@DVDD=3.3V	-	(100)	(150)	mA

1.5 Optical Characteristics

TFT LCD Module

DVDD= 3.3 V, Ta=25°C

Item	Symbol		Condition	Min.	Typ.	Max.	unit	-
Response time	Tr+Tf		Ta = 25°C θX, θY = 0°	-	30	45	ms	Note 2
Viewing angle	Top	θY+	CR ≥ 10		80	-	Deg.	Note 4
	Bottom	θY-			80	-		
	Left	θX-			80	-		
	Right	θX+			80	-		
Contrast ratio	CR			500	600	-	-	Note 3
Color of CIE Coordinate (With B/L)	White	X	Ta = 25°C θX , θY = 0°	-	(0.29)	-	-	Note1
		Y		-	(0.37)	-		
	Red	X		-	(0.59)	-		
		Y		-	(0.37)	-		
	Green	X		-	(0.32)	-		
		Y		-	(0.59)	-		
	Blue	X		-	(0.13)	-		
		Y		-	(0.14)	-		
Average Brightness Pattern=white display (With B/L) *1	IV		IF=(160)mA	(300)	(370)	-	cd/m2	Note1
Uniformity (With B/L) *2	Δ B		IF=(160)mA	70	-	-	%	Note1

Note 1:

*1: $\Delta B = B(\min) / B(\max) * 100\%$


*2: Measurement Condition for Optical Characteristics:

a: Environment: $25^{\circ}\text{C} \pm 5^{\circ}\text{C}$ / $60 \pm 20\%$ R.H, no wind, dark room below 10 Lux at typical lamp current and typical operating frequency

b: Measurement Distance: 500 ± 50 mm, ($\theta = 0^{\circ}$)

c: Equipment: TOPCON BM-7 fast, (field 1°), after 10 minutes operation

d: The uncertainty of the C.I.E coordinate measurement ± 0.01 , Average Brightness $\pm 4\%$



To be measured at the center area of panel with a viewing cone of 1° by Topcon luminance meter BM-7, after 10 minutes operation (module)

Note 2: Definition of response time:


The output signals of photo detector are measured when the input signals are changed from "black" to "white" (falling time) and from "white" to "black" (rising time), respectively. The response time is defined as the time interval between the 10% and 90% of Amplitudes.

Refer to figure as below:

Normally White



Normally Black




Note 3: Definition of contrast ratio:

Contrast ratio is calculated with the following formula

$$\text{Contrast ratio (CR)} = \frac{\text{Photo detector output when LCD is at "White" state}}{\text{Photo detector output when LCD is at "Black" state}}$$

Note 4: Definition of viewing angle:

Refer to figure as below:



1.6 Backlight Characteristics

Maximum Ratings

<u>Item</u>	<u>Symbol</u>	<u>Min.</u>	<u>Max.</u>	<u>Unit</u>	<u>Remark</u>
LED Forward Current	I_F	-	(30*8)	mA	
LED Reverse Voltage	V_R	-	(5.0)	V	
Power Dissipation	PD		(2400)	mW	


Electrical / Optical Characteristics

Electrical / Optical Characteristics						
<u>Item</u>	<u>Symbol</u>	<u>Conditions</u>	<u>Min.</u>	<u>Typ.</u>	<u>Max.</u>	<u>Unit</u>
Forward Voltage	VF	IF= (160) mA	(9.0)	(9.6)	(10.2)	V
Average Brightness (Without LCD)	IV		(6300)	(7560)	-	cd/m ²
CIE Color Coordinate (Without LCD)	X		(0.25)	-	(0.31)	-
	Y		(0.26)	-	(0.32)	
Color	White					

Note 1: The LED Supply Voltage is defined by the number of LED at $T_a = 25^\circ\text{C}$ and $I_L = (160) \text{ mA}$.

Note 2: The "LED life time" is defined as the module brightness decrease to 50% original brightness at $T_a = 25^\circ\text{C}$ and $I_L = (160) \text{ mA}$. The LED life time could be decreased if operating I_L is larger than (160)mA.

B/L Internal Circuit Diagram



Other Description

<u>Item</u>	<u>Conditions</u>	<u>Description</u>
Life Time	$T_a = 25^\circ\text{C}$ $I_F = (160) \text{ mA}$	20,000 hrs


2. Module Structure

2.1 Counter Drawing

2.1.1 LCM Mechanical Diagram

* See Appendix

2.1.2 Block Diagram



2.2 Interface Pin Description

TFT LCM Interface

Pin#	Name	Description
1	VLED+	Power For LED backlight (+).
2	VLED+	Power For LED backlight (+).
3	VLED-	Power For LED backlight (-).
4	VLED-	Power For LED backlight (-).
5	GND	Power ground.
6	VCOM	No Function,Not Connection
7	DVDD	Power for Digital Circuit.
8	MODE	No Function,Not Connection
9	DE	Input data enable control. When DE mode, active High to enable data
10	VS	Vertical sync signal. Negative polarity
11	HS	Horizontal sync signal. Negative polarity
12	B7	Blue Data (MSB).
13	B6	Blue Data.
14	B5	Blue Data.
15	B4	Blue Data.
16	B3	Blue Data.
17	B2	Blue Data.
18	B1	Blue Data.
19	B0	Blue Data (LSB).
20	G7	Green Data (MSB).
21	G6	Green Data.
22	G5	Green Data.
23	G4	Green Data.
24	G3	Green Data.
25	G2	Green Data.
26	G1	Green Data.
27	G0	Green Data (LSB).
28	R7	Red Data (MSB).
29	R6	Red Data.

<u>Pin#</u>	<u>Name</u>	<u>Description</u>
30	R5	Red Data.
31	R4	Red Data.
32	R3	Red Data.
33	R2	Red Data.
34	R1	Red Data.
35	R0	Red Data (LSB).
36	GND	Power Ground
37	DCLK	Sample clock. Latch data at DCLK falling edge.
38	GND	Power Ground.
39	L/R	Horizontal scan direction control.
40	U/D	Vertical scan direction control
41	VGH	No Function,Not Connection
42	VGL	No Function,Not Connection
43	AVDD	No Function,Not Connection
44	RESET	Global reset pin. Low active.
45	NC	No connection.
46	VCOM	No Function,Not Connection
47	DITHB	No Function,Not Connection
48	GND	Power Ground.
49	NC	No connection.
50	NC	No connection.


2.3 Timing Characteristics

2.3.1 RGB Mode Selection Table


<u>RGB Mode Selection Table</u>	<u>DCLK</u>	<u>HSYNC</u>	<u>VSYNC</u>	<u>DE</u>
SYNC - DE Mode	Input	Input	Input	Input
SYNC Mode	Input	Input	Input	GND
DE Mode	Input	GND	GND	Input

Note: "Input" means these signals are driven by host side


2.3.2 SYNC Mode



2.3.3 SYNC-DE Mode



2.3.4 DE Mode




2.3.5 Parallel 24-bit RGB Input Timing Table

Parallel 24-bit RGB Interface Timing Table							
Item		Symbol	Min.	Typ.	Max.	Unit	Remark
DCLK Frequency		Fclk	23	25	27	MHz	
HS	Period Time	Th	808	816	896	DCLK	
	Display Period	Thdisp	800			DCLK	
	Back Porch	Thbp	4	8	24	DCLK	
	Front Porch	Thfp	4	8	24	DCLK	
	Pulse Width	Thw	2	4	8	DCLK	
VS	Period Time	Tv	496	512	528	HSYNC	
	Display Period	Tvdisp	480			HSYNC	
	Back Porch	Tvbp	8	16	24	HSYNC	
	Front Porch	Tvfp	8	16	24	HSYNC	
	Pulse Width	Tvw	2	4	8	HSYNC	

2.3.6 Power On Sequence

1 Power Mode




Symbol	Description	Min. Time	Unit
T0	System power stability to /RESET signal	≥ 1	ms
T1	/RESET= "High" to DISP="High"	≥ 10	ms
T2	DISP="High" to Source/GIP scan blank	85	ms
T3	IC scan blanking signal	≥ 33	ms
T4	Display Signal output to Backlight Power on	≥ 100	ms

Note: 1. When DISP pull "H" or "L", IC will execute the internal power on or power off procedures. Please be careful about the timing of DISP and do not interrupt it during power on or power off procedure, otherwise unexpected errors will occur.

2. RGB interface Display signal: DCLK; VS; HS; DE; R[7:0]; G[7:0]; B[7:0].

2.3.7 Power Off Sequence

1 Power Mode





Symbol	Description	Min. Time	Unit
T0	Backlight Power off to DISP="Low"	≥ 1	ms
T1	DISP="Low" to IC internal voltage discharge complete	≥ 100	ms
T2	DISP="Low" to Source/GIP scan blank (base on Display Signal Frame Rate 60Hz)	≤ 50	ms
T3	IC internal voltage discharge is completed to VDD off	≥ 0	ms

Note: 1. When DISP pull "H" or "L", IC will execute the internal power on or power off procedures. Please be careful about the timing of DISP and do not interrupt it during power on or power off procedure, otherwise unexpected errors will occur.



2. RGB interface Display signal: DCLK; VS; HS; DE; R[7:0]; G[7:0]; B[7:0].

2.5 Reset timing

1.The /RESET pin with external RC circuit.





(2) The GRB pin controlled by MCU.



3. Quality Assurance System

3.1 Quality Assurance Flow Chart




Item	Customer	Sales	R&D	Q.A	Manufacturing	Product control	Purchase	Inventory control
Sales Service	 <pre> graph TD Info[Info] --> Claim[Claim] Claim --> Failure[Failure analysis] Failure --> Analysis[Analysis report] Failure --> Corrective[Corrective action] Corrective --> Tracking[Tracking] </pre>							
Q.A Activity	<ol style="list-style-type: none"> 1. ISO 9001 Maintenance Activities 2. Process improvement proposal 3. Equipment calibration 4. Education And Training Activities 5. Standardization Management 							

3.2 Inspection Specification


- ◆Scope: The document shall be applied to TFT-LCD Module for 3.5" -15" (Ver.B01).
- ◆Inspection Standard: MIL-STD-105E Table Normal Inspection Single Sampling Level II.
- ◆Equipment: Gauge, MIL-STD, Powertip Tester, Sample
- ◆Defect Level: Major Defect AQL: 0.4; Minor Defect AQL: 1.5
- ◆OUT Going Defect Level: Sampling
- ◆Standard of the product appearance test:

a. Manner of appearance test:

- (1). The test best be under 20W×2 fluorescent light(about 300lux ~500lux)
and distance of view must be at 30~40 cm.
- (2). The test direction is base on about around 45° of vertical line.



(3). Definition of area.



A area: viewing area

B area: Outside of viewing area



(4). Standard of inspection : (Unit : mm)

◆Specification For TFT-LCD Module 3.5"~15":


(Ver.B01)

NO	Item	Criterion	Level												
01	Product condition	1.1 The part number is inconsistent with work order of production.	Major												
		1.2 Mixed product types.	Major												
		1.3 Assembled in inverse direction.	Major												
02	Quantity	2.1 The quantity is inconsistent with work order of production.	Major												
03	Outline dimension	3.1 Product dimension and structure must conform to structure diagram.	Major												
04	Electrical Testing	4.1 Missing line character and icon.	Major												
		4.2 No function or no display.	Major												
		4.3 Display malfunction.	Major												
		4.4 LCD viewing angle defect.	Major												
		4.5 Current consumption exceeds product specifications.	Major												
		4.6 Mura cannot be seen through 5% ND filter at 50% Gray, should be judged by the viewing angle of 90 degree.	Minor												
05	Dot defect (Bright dot, Dark dot) On -display	<table><tr><th colspan="2">Item</th><th>Acceptance (Q'ty)</th></tr><tr><td rowspan="4">Dot Defect</td><td>Bright Dot</td><td>≤ 4</td></tr><tr><td>Dark Dot</td><td>≤ 5</td></tr><tr><td>Joint Dot</td><td>≤ 3</td></tr><tr><td>Total</td><td>≤ 7</td></tr></table>	Item		Acceptance (Q'ty)	Dot Defect	Bright Dot	≤ 4	Dark Dot	≤ 5	Joint Dot	≤ 3	Total	≤ 7	Minor
		Item		Acceptance (Q'ty)											
Dot Defect	Bright Dot	≤ 4													
	Dark Dot	≤ 5													
	Joint Dot	≤ 3													
	Total	≤ 7													
5.1 Inspection pattern: full white, full black, Red, Green and blue screens. 5.2 It is defined as dot defect if defect area > 1/2 dot. 5.3 The distance between two dot defect ≥ 5 mm. 5.4 Bright dot : Dots appear bright and unchanged in visible with 5% ND filter is defined. 5.5 Tiny bright dot: bright dot area ≤ 1/2 dot. a. Dots appear bright and unchanged in visible with 5% ND filter is defined defect and is judged in accordance with 6.1 b. Dots invisible with 5% ND Filter is Ignored.															



◆Specification For TFT-LCD Module 3.5" ~15" :
(Ver.B01)

NO	Item	Criterion	Level																																			
06	Black or white Dot, scratch, contamination Round type  Φ = (x + y) / 2 Line type 	6.1 Round type (Non-display or display): <table><thead><tr><th rowspan="2">Dimension (diameter: Φ)</th><th colspan="2">Acceptance (Q'ty)</th></tr><tr><th>A area</th><th>B area</th></tr></thead><tbody><tr><td>Φ ≤ 0.25</td><td>Ignore</td><td rowspan="4">Ignore</td></tr><tr><td>0.25 < Φ ≤ 0.50</td><td>5</td></tr><tr><td>Φ > 0.50</td><td>0</td></tr><tr><td>Total</td><td>5</td></tr></tbody></table>	Dimension (diameter: Φ)	Acceptance (Q'ty)		A area	B area	Φ ≤ 0.25	Ignore	Ignore	0.25 < Φ ≤ 0.50	5	Φ > 0.50	0	Total	5	Minor																					
		Dimension (diameter: Φ)		Acceptance (Q'ty)																																		
			A area	B area																																		
		Φ ≤ 0.25	Ignore	Ignore																																		
0.25 < Φ ≤ 0.50	5																																					
Φ > 0.50	0																																					
Total	5																																					
6.2 Line type(Non-display or display): <table><thead><tr><th rowspan="2">module size</th><th rowspan="2">Length (L)</th><th rowspan="2">Width (W)</th><th colspan="2">Acceptance (Q'ty)</th></tr><tr><th>A area</th><th>B area</th></tr></thead><tbody><tr><td rowspan="5">3.5" to less 9"</td><td>---</td><td>W ≤ 0.03</td><td>Ignore</td><td rowspan="5">Ignore</td></tr><tr><td>L ≤ 10.0</td><td>0.03 < W ≤ 0.05</td><td>4</td></tr><tr><td>L ≤ 5.0</td><td>0.05 < W ≤ 0.10</td><td>2</td></tr><tr><td>---</td><td>W > 0.10</td><td>As round type</td></tr><tr><td colspan="2">Total</td><td>5</td></tr><tr><td rowspan="4">9" to 15"</td><td>---</td><td>W ≤ 0.05</td><td>Ignore</td><td rowspan="4">Ignore</td></tr><tr><td>L ≤ 10.0</td><td>0.05 < W ≤ 0.10</td><td>5</td></tr><tr><td>---</td><td>W > 0.10</td><td>As round type</td></tr><tr><td colspan="2">Total</td><td>5</td></tr></tbody></table>	module size	Length (L)	Width (W)	Acceptance (Q'ty)		A area	B area	3.5" to less 9"	---	W ≤ 0.03	Ignore	Ignore	L ≤ 10.0	0.03 < W ≤ 0.05	4	L ≤ 5.0	0.05 < W ≤ 0.10	2	---	W > 0.10	As round type	Total		5	9" to 15"	---	W ≤ 0.05	Ignore	Ignore	L ≤ 10.0	0.05 < W ≤ 0.10	5	---	W > 0.10	As round type	Total		5
module size				Length (L)	Width (W)	Acceptance (Q'ty)																																
	A area	B area																																				
3.5" to less 9"	---	W ≤ 0.03	Ignore	Ignore																																		
	L ≤ 10.0	0.03 < W ≤ 0.05	4																																			
	L ≤ 5.0	0.05 < W ≤ 0.10	2																																			
	---	W > 0.10	As round type																																			
	Total		5																																			
9" to 15"	---	W ≤ 0.05	Ignore	Ignore																																		
	L ≤ 10.0	0.05 < W ≤ 0.10	5																																			
	---	W > 0.10	As round type																																			
	Total		5																																			
07	Polarizer Bubble	<table><thead><tr><th rowspan="2">Dimension (diameter: Φ)</th><th colspan="2">Acceptance (Q'ty)</th></tr><tr><th>A area</th><th>B area</th></tr></thead><tbody><tr><td>Φ ≤ 0.25</td><td>Ignore</td><td rowspan="5">Ignore</td></tr><tr><td>0.25 < Φ ≤ 0.50</td><td>4</td></tr><tr><td>0.50 < Φ ≤ 0.80</td><td>1</td></tr><tr><td>Φ > 0.80</td><td>0</td></tr><tr><td>Total</td><td>5</td></tr></tbody></table>	Dimension (diameter: Φ)	Acceptance (Q'ty)		A area	B area	Φ ≤ 0.25	Ignore	Ignore	0.25 < Φ ≤ 0.50	4	0.50 < Φ ≤ 0.80	1	Φ > 0.80	0	Total	5	Minor																			
Dimension (diameter: Φ)	Acceptance (Q'ty)																																					
	A area	B area																																				
Φ ≤ 0.25	Ignore	Ignore																																				
0.25 < Φ ≤ 0.50	4																																					
0.50 < Φ ≤ 0.80	1																																					
Φ > 0.80	0																																					
Total	5																																					

◆Specification For TFT-LCD Module 3.5" ~15" :
(Ver.B01)

NO	Item	Criterion	Level									
08	The crack of glass	<p>Symbols :</p> <p>X: The length of crack Z: The thickness of crack T: The thickness of glass</p> <p>Y: The width of crack. W: terminal length a : LCD side length</p> <p>8.1 General glass chip: 8.1.1 Chip on panel surface and crack between panels:</p>  <table><thead><tr><th>X</th><th>Y</th><th>Z</th></tr></thead><tbody><tr><td>$\leq a$</td><td>Crack can't enter viewing area</td><td>$\leq 1/2 t$</td></tr><tr><td>$\leq a$</td><td>Crack can't exceed the half of SP width.</td><td>$1/2 t < Z \leq 2 t$</td></tr></tbody></table>	X	Y	Z	$\leq a$	Crack can't enter viewing area	$\leq 1/2 t$	$\leq a$	Crack can't exceed the half of SP width.	$1/2 t < Z \leq 2 t$	Minor
X	Y	Z										
$\leq a$	Crack can't enter viewing area	$\leq 1/2 t$										
$\leq a$	Crack can't exceed the half of SP width.	$1/2 t < Z \leq 2 t$										

◆Specification For TFT-LCD Module 3.5" ~15" :
(Ver.B01)

NO	Item	Criterion	Level									
08	The crack of glass	<p>Symbols :</p> <p>X: The length of crack Z: The thickness of crack t: The thickness of glass</p> <p>Y: The width of crack. W: terminal length a: LCD side length</p> <p>8.1.2 Corner crack:</p>  <table><thead><tr><th>X</th><th>Y</th><th>Z</th></tr></thead><tbody><tr><td>$\leq 1/5 a$</td><td>Crack can't enter viewing area</td><td>$Z \leq 1/2 t$</td></tr><tr><td>$\leq 1/5 a$</td><td>Crack can't exceed the half of SP width.</td><td>$1/2 t < Z \leq 2 t$</td></tr></tbody></table>	X	Y	Z	$\leq 1/5 a$	Crack can't enter viewing area	$Z \leq 1/2 t$	$\leq 1/5 a$	Crack can't exceed the half of SP width.	$1/2 t < Z \leq 2 t$	Minor
		X	Y	Z								
$\leq 1/5 a$	Crack can't enter viewing area	$Z \leq 1/2 t$										
$\leq 1/5 a$	Crack can't exceed the half of SP width.	$1/2 t < Z \leq 2 t$										
<p>8.2 Protrusion over terminal:</p> <p>8.2.1 Chip on electrode pad:</p>  <table><thead><tr><th></th><th>X</th><th>Y</th><th>Z</th></tr></thead><tbody><tr><td>Front</td><td>$\leq a$</td><td>$\leq 1/2 W$</td><td>$\leq t$</td></tr><tr><td>Back</td><td>$\leq a$</td><td>$\leq W$</td><td>$\leq 1/2 t$</td></tr></tbody></table>		X	Y	Z	Front	$\leq a$	$\leq 1/2 W$	$\leq t$	Back	$\leq a$	$\leq W$	$\leq 1/2 t$
	X	Y	Z									
Front	$\leq a$	$\leq 1/2 W$	$\leq t$									
Back	$\leq a$	$\leq W$	$\leq 1/2 t$									

◆Specification For TFT-LCD Module 3.5" ~15" :
(Ver.B01)

NO	Item	Criterion	Level												
08	The crack of glass	<div> <div> <p>Symbols:</p> <p>X: The length of crack</p> <p>Z: The thickness of crack</p> <p>t: The thickness of glass</p> </div> <div> <p>Y: The width of crack.</p> <p>W: terminal length</p> <p>a: LCD side length</p> </div> </div> <hr/> <p>8.2.2 Non-conductive portion:</p> <table border="1"> <thead> <tr> <th><u>X</u></th> <th><u>Y</u></th> <th><u>Z</u></th> </tr> </thead> <tbody> <tr> <td>$\leq 1/3 a$</td> <td>$\leq W$</td> <td>$\leq t$</td> </tr> </tbody> </table> <p>If the chipped area touches the ITO terminal, over 2/3 of the ITO must remain and be inspected according to electrode terminal specifications.</p> <p>8.2.3 Glass remain:</p> <table border="1"> <thead> <tr> <th><u>X</u></th> <th><u>Y</u></th> <th><u>Z</u></th> </tr> </thead> <tbody> <tr> <td>$\leq a$</td> <td>$\leq 1/3 W$</td> <td>$\leq t$</td> </tr> </tbody> </table> <p>8.2.4 Cracking:</p> <p>Not Allowed</p>	<u>X</u>	<u>Y</u>	<u>Z</u>	$\leq 1/3 a$	$\leq W$	$\leq t$	<u>X</u>	<u>Y</u>	<u>Z</u>	$\leq a$	$\leq 1/3 W$	$\leq t$	Minor
<u>X</u>	<u>Y</u>	<u>Z</u>													
$\leq 1/3 a$	$\leq W$	$\leq t$													
<u>X</u>	<u>Y</u>	<u>Z</u>													
$\leq a$	$\leq 1/3 W$	$\leq t$													

◆Specification For TFT-LCD Module 3.5" ~15" :
(Ver.B01)

<u>NO</u>	<u>Item</u>	<u>Criterion</u>	<u>Level</u>
09	Backlight elements	9.1 Backlight can't work normally.	Major
		9.2 Backlight doesn't light or color is wrong.	Major
		9.3 Illumination source flickers when lit.	Major
10	General appearance	10.1 Pin type, quantity, dimension must match type in structure diagram.	Major
		10.2 No short circuits in components on PCB or FPC.	Major
		10.3 Parts on PCB or FPC must be: no wrong parts, missing parts or excess parts.	Major
		10.4 Product packaging must the same as specified on packaging specification sheet.	Minor
		10.5 The folding and peeled off in polarizer are not acceptable.	Minor
		10.6 The PCB or FPC between B/L assembled distance(PCB or FPC) is ≤ 1.5 mm.	Minor

5. PRECAUTION RELATING PRODUCT HANDLING

5.1 SAFETY

- 5.1.1 If the LCD panel breaks, be careful not to get the liquid crystal to touch your skin.
- 5.1.2 If the liquid crystal touches your skin or clothes, please wash it off immediately by using soap and water.

5.2 HANDLING


- 5.2.1 Avoid any strong mechanical shock which can break the glass.
- 5.2.2 Avoid static electricity which can damage the CMOS LSI—When working with the module, be sure to ground your body and any electrical equipment you may be using.
- 5.2.3 Do not remove the panel or frame from the module.
- 5.2.4 The polarizing plate of the display is very fragile. So, please handle it very carefully, do not touch, push or rub the exposed polarizing with anything harder than an HB pencil lead (glass, tweezers, etc.)
- 5.2.5 Do not wipe the polarizing plate with a dry cloth, as it may easily scratch the surface of plate.
- 5.2.6 Do not touch the display area with bare hands, this will stain the display area.
- 5.2.7 Do not use ketonic solvent & aromatic solvent. Use with a soft cloth soaked with a cleaning naphtha solvent.
- 5.2.8 To control temperature and time of soldering is $320 \pm 10^{\circ}\text{C}$ and 3 ~ 5 sec.
- 5.2.9 To avoid liquid (include organic solvent) stained on LCM.
- 5.2.10 Caution! (LCM products with Capacitive Touch Panel)
Strong EMI-sources such as switch-mode power supplies (SPS) can lead to touch malfunction (e.g., ghost-touches). Therefore, the touch needs to be thoroughly tested inside the target application.
- 5.2.11 CAUTION: Continuously displaying same static image will result in high possibility of image sticking/image burn-in effect due to TFT panel characteristic.
- 5.2.12 Double-sided tape designed to be attached with the customer's mechanical device, please follow up the rules and regulations published by the original manufacturer of double-side tape for the attachment operation.

5.3 STORAGE


- 5.3.1 Store the panel or module in a dark place where the temperature is $25^{\circ}\text{C} \pm 5^{\circ}\text{C}$ and the humidity is below 65% RH.
- 5.3.2 Do not place the module near organics solvents or corrosive gases.
- 5.3.3 Do not crush, shake, or jolt the module.


5.4 TERMS OF WARRANTY

- 5.4.1 Applicable **warrant** period
The period is **within** thirteen months since the date of shipping out under normal using and storage **conditions**.
- 5.4.2 Unaccepted **responsibility**
This product has been manufactured to your company's specification as a part for use in your company's general electronic products. It is guaranteed to perform according to delivery specifications. For any other use apart from general electronic equipment, we cannot take responsibility if the product is used in nuclear power control equipment, aerospace equipment, fire and security systems or any other applications in which there is a direct risk to human life and where extremely high levels of reliability are required.



- NOTES:
- 1.LCD TYPE: IPS LCD
 - 2.LCD DISPLAY: Normally Black/Transmissive
 - 3.The tolerance unless classified ±0.3mm
 - 4.LCM FPC Matching Connector: FH12A-50S-0.5SH (Hirose) or Compatible
 5. Component Area; Aluminum Foil Conductive Adhesive Tape; Kapton tape; EMI; Stiffener



007				PART NO:	PH800480T037-ZZA															
006					DRAWING NAME : LMD-PH800480T037-ZZA															
005					TITLE: LCD MODULE DRAWING															
004					Design	Kevin		(3)	Surface	<div><div><div></div><div></div><div></div><div></div></div><div>久正光电股份有限公司</div><div>POWER TIP TECHNOLOGY CORPORATION</div></div>					Precision Level					
003																				
002					Check	Stone														
001	NEW DRAWING	Kevin	2023/12/12				Unit	MM	Material											
REV							Scale	1:1	Thickness											
	REV BY	REVISER	DATE		Approve	Rex	Page	1/1	Quantity											