Product data sheet Characteristics

PRA24213

Pragma flush enclosure - IP40 - 2 x 13 modules - transparent door





Main

Range	Pragma
Product or component type	Enclosure
Enclosure type	Distribution enclosure
Width	366 Mm wall: 396 Mm outside:
Height	480 Mm wall: 510 Mm outside:
Depth	41 Mm outside: 86 Mm wall:
Number of 18 mm modules per row	13
Number of horizontal rows	2
Electrical insulation class	Class II Double insulation
Provided equipment	2 x terminal block 1 x identification label 1 x marking kit 1 x blanking plate strip
Type of front cover	Transparent

Complementary

Enclosure mounting	Flush
9 mm pitches	26
Total number of 18 mm modules	26
Power dissipation in W	50 W
[In] rated current	63 A
Type of rail	DIN
Mounting plate description	Without mounting plate
Cable entry	Side pre-cutouts Cable or tube Removable plates
Number of terminal blocks	1 earth (Quick) with 24 outgoers 1 neutral (Quick) with 24 outgoers
Distribution block outgoers	3 x 25 mm² for earth 21 x 4 mm² for earth 3 x 25 mm² for neutral 21 x 4 mm² for neutral
Enclosure material	Back part: technoplastic Door: technoplastic Front face: technoplastic

N.I	F. de	
Colour	Enclosure: white (RAL 9016) Front face: grey (RAL 7004)	
	Door: colourless	
Market segment	Small commercial Residential	
Embedding depth	86 Mm	
nternal depth	84 Mm	
Environment		
Fire resistance	Back part: 650 °C Front face: 650 °C Door: 650 °C	
P degree of protection	IP30 without door IP40 with door	
K degree of protection	IK08 without door IK09 with door	
Overvoltage category	II	
Ambient air temperature for operation	-2560 °C	
Standards	IEC 60670-1 IEC 60670-24 IEC 61439-1 IEC 61439-3	
Packing Units		
Jnit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	17.500 Cm	
Package 1 Width	41.000 Cm	
Package 1 Length	52.000 Cm	
Package 1 Weight	4.399 Kg	
Jnit Type of Package 2	P12	
Number of Units in Package 2	16	
Package 2 Height	90.000 Cm	
· · · · · · · · · · · · · · · · · · ·	00 000 0	·
Package 2 Width	80.000 Cm	
Package 2 Width Package 2 Length	120.000 Cm	

Offer Sustainability

Oner Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₽¥Yes
Environmental Disclosure	

Contractual warranty

Warranty 18 months

Product Life Status: End of commerc. announced



PRA24213 may be replaced by any of the following products:



LVSXP213

Modular enclosure, PrismaSeT XS, flush, 2 x 13 modules, 1 earth + 1 neutral terminal blocks, transparent smoked do Qty 1

Substitution date: |