Product data sheet Characteristics

PRA24313

Pragma flush enclosure - IP40 - 3 x 13 modules - transparent door





Main

Range	Pragma
Product or component type	Enclosure
Enclosure type	Distribution enclosure
Width	366 Mm wall: 396 Mm outside:
Height	630 Mm wall: 660 Mm outside:
Depth	41 Mm outside: 86 Mm wall:
Number of 18 mm modules per row	13
Number of horizontal rows	3
Electrical insulation class	Class II Double insulation
Provided equipment	2 x terminal block 1 x identification label 1 x marking kit 1 x blanking plate strip
Type of front cover	Transparent

Complementary

Enclosure mounting	Flush
9 mm pitches	26
Total number of 18 mm modules	39
Power dissipation in W	56 W
[In] rated current	90 A
Type of rail	DIN
Mounting plate description	Without mounting plate
Cable entry	Side pre-cutouts Cable or tube Removable plates
Number of terminal blocks	1 earth (Quick) with 24 outgoers 1 neutral (Quick) with 24 outgoers
Distribution block outgoers	3 x 25 mm² for earth 21 x 4 mm² for earth 3 x 25 mm² for neutral 21 x 4 mm² for neutral
Enclosure material	Back part: technoplastic Door: technoplastic Front face: technoplastic

Colour	Enclosure: white (RAL 9016) Front face: grey (RAL 7004) Door: colourless
Market segment	Small commercial Residential
Embedding depth	86 Mm
Internal depth	84 Mm
Environment	
Fire resistance	Back part: 650 °C Front face: 650 °C Door: 650 °C
IP degree of protection	IP30 without door IP40 with door
IK degree of protection	IK08 without door IK09 with door
Overvoltage category	II
Ambient air temperature for operation	-2560 °C
Standards	IEC 60670-1 IEC 60670-24 IEC 61439-1 IEC 61439-3
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.000 Cm
Package 1 Width	41.000 Cm
Package 1 Length	67.000 Cm
Package 1 Weight	5.372 Kg
Unit Type of Package 2	P12
Number of Units in Package 2	17
Package 2 Height	160.000 Cm
Package 2 Width	80.000 Cm
Package 2 Length	120.000 Cm
Package 2 Weight	103.324 Kg

Offer Sustainability

Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) E EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	☑ Product Environmental Profile

Contractual warranty

Warranty 18 months

Product Life Status: End of commerc. announced



PRA24313 may be replaced by any of the following products:



LVSXP313

Modular enclosure, PrismaSeT XS, flush, 3 x 13 modules, 1 earth + 1 neutral terminal blocks, transparent smoked do Qty 1

Substitution date: |