



### Main

Range	Pragma
Product or component type	Enclosure
Enclosure type	Distribution enclosure
Width	456 Mm wall: 486 Mm outside:
Height	630 Mm wall: 660 Mm outside:
Depth	86 Mm wall: 43 Mm outside:
Number of 18 mm modules per row	18
Number of horizontal rows	3
Electrical insulation class	Class II Double insulation
Provided equipment	2 x terminal block 1 x identification label 1 x marking kit 1 x blanking plate strip
Type of front cover	Transparent

### Complementary

Enclosure mounting	Flush
9 mm pitches	36
Total number of 18 mm modules	54
Power dissipation in W	68 W
[In] rated current	125 A
Type of rail	DIN
Mounting plate description	Without mounting plate
Cable entry	Side pre-cutouts Removable plates Cable or tube
Number of terminal blocks	1 earth (Quick) with 24 outgoing 1 neutral (Quick) with 24 outgoing
Distribution block outgoing	3 x 25 mm <sup>2</sup> for earth 21 x 4 mm <sup>2</sup> for earth 3 x 25 mm <sup>2</sup> for neutral 21 x 4 mm <sup>2</sup> for neutral
Enclosure material	Back part: technoplastic Door: technoplastic Front face: technoplastic

Colour	Enclosure: white (RAL 9016) Front face: grey (RAL 7004) Door: colourless
Market segment	Small commercial Residential
Embedding depth	86 Mm
Internal depth	84 Mm

## Environment

Fire resistance	Back part: 650 °C Front face: 650 °C Door: 650 °C
IP degree of protection	IP30 without door IP40 with door
IK degree of protection	IK08 without door IK09 with door
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C
Standards	IEC 60670-1 IEC 60670-24 IEC 61439-1 IEC 61439-3

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19.000 Cm
Package 1 Width	50.000 Cm
Package 1 Length	68.000 Cm
Package 1 Weight	6.371 Kg
Unit Type of Package 2	P12
Number of Units in Package 2	10
Package 2 Height	160.000 Cm
Package 2 Width	80.000 Cm
Package 2 Length	120.000 Cm
Package 2 Weight	75.710 Kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **End of commerc. announced**

PRA24318 may be replaced by any of the following products:

---



**LVSXP318**

Modular enclosure, PrismaSeT XS, flush, 3 x 18 modules, 1 earth + 1 neutral terminal blocks, transparent smoked door

Qty 1

Substitution date: |

---