



### Main

|                                 |   |
|---------------------------------|---|
| Range                           | Pragma  |
| Product or component type       | Enclosure   |
| Enclosure type                  | Distribution enclosure  |
| Width                           | 366 Mm wall:<br>396 Mm outside:   |
| Height                          | 780 Mm wall:<br>810 Mm outside:   |
| Depth                           | 41 Mm outside:<br>86 Mm wall:   |
| Number of 18 mm modules per row | 13  |
| Number of horizontal rows       | 4   |
| Electrical insulation class     | Double insulation<br>Class II   |
| Provided equipment              | 2 x terminal block<br>1 x identification label<br>1 x marking kit<br>1 x blanking plate strip |
| Type of front cover             | Transparent   |

### Complementary

|                               |  |
|-------------------------------|--|
| Enclosure mounting            | Flush  |
| 9 mm pitches                  | 26   |
| Total number of 18 mm modules | 52   |
| Power dissipation in W        | 76 W   |
| [In] rated current            | 90 A   |
| Type of rail                  | DIN  |
| Mounting plate description    | Without mounting plate   |
| Cable entry                   | Cable or tube<br>Side pre-cutouts<br>Removable plates  |
| Number of terminal blocks     | 1 earth (Quick) with 24 outgoers<br>1 neutral (Quick) with 24 outgoers   |
| Distribution block outgoers   | 3 x 25 mm <sup>2</sup> for earth<br>21 x 4 mm <sup>2</sup> for earth<br>3 x 25 mm <sup>2</sup> for neutral<br>21 x 4 mm <sup>2</sup> for neutral |
| Enclosure material            | Back part: technoplastic<br>Door: technoplastic<br>Front face: technoplastic   |

|                 |  |
|-----------------|--|
| Colour          | Enclosure: white (RAL 9016)<br>Front face: grey (RAL 7004)<br>Door: colourless |
| Market segment  | Residential<br>Small commercial  |
| Embedding depth | 86 Mm  |
| Internal depth  | 84 Mm  |

## Environment

|                                       |   |
|---------------------------------------|---|
| Fire resistance                       | Back part: 650 °C<br>Front face: 650 °C<br>Door: 650 °C   |
| IP degree of protection               | IP30 without door<br>IP40 with door                       |
| IK degree of protection               | IK08 without door<br>IK09 with door                       |
| Overvoltage category                  | II  |
| Ambient air temperature for operation | -25...60 °C   |
| Standards                             | IEC 60670-1<br>IEC 60670-24<br>IEC 61439-1<br>IEC 61439-3 |

## Packing Units

|                              |            |
|------------------------------|------------|
| Unit Type of Package 1       | PCE        |
| Number of Units in Package 1 | 1          |
| Package 1 Height             | 18.000 Cm  |
| Package 1 Width              | 42.000 Cm  |
| Package 1 Length             | 82.500 Cm  |
| Package 1 Weight             | 6.849 Kg   |
| Unit Type of Package 2       | P12        |
| Number of Units in Package 2 | 9          |
| Package 2 Height             | 90.000 Cm  |
| Package 2 Width              | 80.000 Cm  |
| Package 2 Length             | 120.000 Cm |
| Package 2 Weight             | 73.641 Kg  |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product  |
| REACH Regulation           | <a href="#">REACH Declaration</a>  |
| REACH free of SVHC         | Yes  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes  |
| Mercury free               | Yes  |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>   |
| RoHS exemption information | <a href="#">Yes</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **End of commerc. announced**

PRA24413 may be replaced by any of the following products:

---



**LVSXP413**

Modular enclosure, PrismaSeT XS, flush, 4 x 13 modules, 1 earth + 1 neutral terminal blocks, transparent smoked door

Qty 1

Substitution date: |

---