



### Commercial status

End-of-Sale Notice : JUN 30, 2023

 End-of-Sale Notice

### Main

Range	Pragma
Product or component type	Enclosure
Enclosure type	Distribution enclosure
Width	426 Mm outside:
Height	300 Mm
Depth	145 Mm
Number of 18 mm modules per row	18
Number of horizontal rows	1
Electrical insulation class	Double insulation Class II
Provided equipment	2 x terminal block 1 x identification label 1 x marking kit 1 x blanking plate strip
Type of front cover	Plain

### Complementary

Enclosure mounting	Surface
9 mm pitches	36
Total number of 18 mm modules	18
Power dissipation in W	33 W
[In] rated current	90 A
Type of rail	DIN
Mounting plate description	Without mounting plate
Cable entry	Cable or tube Trunking Removable plates Cut-out plates
Number of terminal blocks	1 earth (Quick) with 24 outgoing 1 neutral (Quick) with 14 outgoing
Distribution block outgoing	3 x 25 mm <sup>2</sup> for earth 21 x 4 mm <sup>2</sup> for earth 3 x 25 mm <sup>2</sup> for neutral 11 x 4 mm <sup>2</sup> for neutral
Enclosure material	Back part: technoplastic Front face: technoplastic

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Colour	Door: white (RAL 9016) Enclosure: white (RAL 9016) Front face: grey (RAL 7004)
Market segment	Small commercial Residential
Embedding depth	0 Mm
Internal depth	95 Mm

## Environment

Fire resistance	Back part: 650 °C Front face: 650 °C Door: 650 °C
IP degree of protection	IP30 without door IP40 with door
IK degree of protection	IK08 without door IK09 with door
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C
Standards	IEC 60670-1 IEC 60670-24 IEC 61439-1 IEC 61439-3

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.5 Cm
Package 1 Width	51.0 Cm
Package 1 Length	38.0 Cm
Package 1 Weight	3.27 Kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **End of commercialisation**