# Product data sheet Characteristics

## PRA30413

Pragma surface enclosure - IP30 - 4 x 13 modules - plain door





#### Commercial status

End-of-Sale Notice: JUN 30, 2023

#### △ End-of-Sale Notice

#### Main

Range	Pragma
Product or component type	Enclosure
Enclosure type	Distribution enclosure
Width	336 Mm outside:
Height	750 Mm
Depth	143 Mm
Number of 18 mm modules per row	13
Number of horizontal rows	4
Electrical insulation class	Class II Double insulation
Provided equipment	2 x terminal block 1 x identification label 1 x marking kit 1 x blanking plate strip
Type of front cover	Plain

### Complementary

Enclosure mounting	Surface
9 mm pitches	26
Total number of 18 mm modules	52
Power dissipation in W	53 W
[In] rated current	90 A
Type of rail	DIN
Cable entry	Cable or tube Cut-out plates Trunking Removable plates
Number of terminal blocks	1 earth (Quick) with 29 outgoers 1 neutral (Quick) with 29 outgoers
Distribution block outgoers	4 x 25 mm² for earth 25 x 4 mm² for earth 4 x 25 mm² for neutral 25 x 4 mm² for neutral
Enclosure material	Back part: technoplastic Front face: technoplastic

Colour	Door: white (RAL 9016)
	Enclosure: white (RAL 9016) Front face: grey (RAL 7004)
Market segment	Small commercial Residential
Environment	
Fire resistance	Back part: 650 °C Front face: 650 °C Door: 650 °C
IP degree of protection	IP30 without door IP40 with door
IK degree of protection	IK08 without door IK09 with door
Overvoltage category	II
Ambient air temperature for operation	-2560 °C
Standards	IEC 60670-1 IEC 60670-24 IEC 61439-1 IEC 61439-3
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	17.5 Cm
Package 1 Width	43.0 Cm
Package 1 Length	84.0 Cm
Package 1 Weight	6.2 Kg
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	<sup>™</sup> REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☐ China RoHS Declaration
RoHS exemption information	₩Yes
Environmental Disclosure	Product Environmental Profile
Contractual warranty	
Warranty	18 months
	.5



End of commercialisation

Product Life Status: