Product data sheet Characteristics

PRA31313

Pragma flush enclosure - IP40 - 3 x 13 modules - plain door





Commercial status

End-of-Sale Notice: JUN 30, 2023

Main

Range	Pragma
Product or component type	Enclosure
Enclosure type	Distribution enclosure
Width	366 Mm wall: 396 Mm outside:
Height	630 Mm wall: 660 Mm outside:
Depth	41 Mm outside: 86 Mm wall:
Number of 18 mm modules per row	13
Number of horizontal rows	3
Electrical insulation class	Class II Double insulation
Provided equipment	2 x terminal block 1 x identification label 1 x marking kit 1 x blanking plate strip
Type of front cover	Plain

Complementary

Enclosure mounting	Flush
9 mm pitches	26
Total number of 18 mm modules	39
Power dissipation in W	56 W
[In] rated current	90 A
[Ui] rated insulation voltage	800 V
Type of rail	DIN
Mounting plate description	Without mounting plate
Cable entry	Side pre-cutouts Removable plates Cable or tube
Number of terminal blocks	1 earth (Quick) with 24 outgoers 1 neutral (Quick) with 24 outgoers
Distribution block outgoers	3 x 25 mm² for earth 21 x 4 mm² for earth 3 x 25 mm² for neutral 21 x 4 mm² for neutral

Enclosure material	Back part: technoplastic Door: technoplastic Front face: technoplastic	
Colour	Door: white (RAL 9016) Enclosure: white (RAL 9016) Front face: grey (RAL 7004)	
Market segment	Residential Small commercial	
Embedding depth	86 Mm	
Internal depth	84 Mm	

Environment

Fire resistance	Back part: 650 °C	
	Front face: 650 °C	
	Door: 650 °C	
IP degree of protection	IP30 without door	
	IP40 with door	
IK degree of protection	IK08 without door	
	IK09 with door	
Overvoltage category	II	
Ambient air temperature for operation	-2560 °C	
Standards	IEC 60670-1	
	IEC 60670-24	
	IEC 61439-1	
	IEC 61439-3	

Packing Units

Heit Town of Doolsons 4	DOE
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19.0 Cm
Package 1 Width	41.5 Cm
Package 1 Length	66.0 Cm
Package 1 Weight	5.855 Kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	[™] REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months

Product Life Status : End of commercialisation

