Date 17.8.2015

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/ UNDERTAKING

- 1.1Product identifier1.1.1Commercial Product Name
PRF Silicon Oil
- **1.1.2 Product code** PISILI52

1.2 Relevant identified uses of the substance or mixture and uses advised against

- 1.2.1 Recommended use
 - Lubricant
- 1.3 Details of the supplier of the safety data sheet
- 1.3.1 Supplier

	Taerosol Oy
Street address	Hampuntie 21
Postcode and post office	36220
Postcode and post office	Kangasala Finland
Telephone	03-3565600
Email	heikki.jalava@taerosol.com

1.4 Emergency telephone number

1.4.1Telephone number, name and address
09-471 977 tai 09-4711 Myrkytystietokeskus / HUS
PL 340 (Haartmaninkatu 4), 00029 HUS (Helsinki)

2. HAZARDS IDENTIFICATION

2.1	Classification of the substance or mixture 1272/2008 (CLP) Flam. Aerosol 1, H222 Flam. Gas 1, H229		
	Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411 67/548/EEC - 1999/45/EC F+, Xi, N; R12-38-51/53		
2.2	Label elements 1272/2008 (CLP) GHS09 - GHS07 - GHS02 Signal word Danger Hazard Statements		

12/2/2008 (CL	
GHS09 - GHS07 -	GHS02
Signal word	Danger
Hazard Stateme	ents 🗸 🗸 🗸
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
Precautionary S	tatements
P102	Keep out of reach of children.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P262	Do not get in eyes, on skin, or on clothing.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C/ 122 °F.

Date 17.8.2015

2.3 Other hazards

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Hazardous componen	ts		
CAS/EC and Reg. number	Chemical name of the substance	Concentratio n	Classification
64742-49-0 265-151-9	Naphtha (petroleum),hydrotreatedlight	30-40%	CLP:Flam.Liq. 2; H225 R 12 Skin.Irrit. 2; H315 R 38 STOT SE 3; H336 R 67 Asp.tox 1; H304 R 65 Aquatic Chronic 2; H411 R 51/53
106-97-8 200-857-2	butan	10-20%	F+; R12 ;Flam. Gas 1, H220; Press. Gas
74-98-6 200-827-9	propan	10-20%	F+; R12 ;Flam. Gas 1, H220; Press. Gas
63148-62-9	Polydimetyylisiloksan	15-25%	-

4. FIRST AID MEASURES

4.1 Description of first aid measures

Do not induce vomiting: contains petroleum distillates and/or aromatic solvents.

4.1.2 Inhalation

In the case of inhalation of aerosol/mist consult a physician if necessary.

4.1.3 Skin contact

Get medical attention if symptoms occur.

4.1.4 Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

4.1.5 Ingestion

If swallowed, call a poison control centre or doctor immediately.

- **4.2 Most important symptoms and effects, both acute and delayed** Aspiration hazard if swallowed can enter lungs and cause damage.
- **4.3** Indication of immediate medical attention and special treatment needed Aspiration hazard

5. FIREFIGHTING MEASURES

- 5.1 Extinguishing media
- 5.1.1 Suitable extinguishing media
 - ABC powder, Alcohol-resistant foam, Carbon dioxide (CO2)
- **5.1.2 Extinguishing media which must not be used for safety reasons** Do NOT use water jet.
- **5.2 Special hazards arising from the substance or mixture** Explosive reaction may occur on heating or burning.

Date 17.8.2015

Previous date: 17.8.2015

5.3 Advice for firefighters Alcohol-resistant foam

5.4 Specific methods Immediately evacuate personnel to safe areas.

6. ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures Prevent unauthorised persons entering the zone. Pay attention to the spreading of gases especially at ground level (heavier than air) and to the direction of the wind.
- 6.2 Environmental precautions Prevent product from entering drains.
- 6.3 Methods and materials for containment and cleaning up not determined
- 6.4 Reference to other sections not determined

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Do not use in areas without adequate ventilation. No sparking tools should be used. Do not taste or swallow. Do not spray on a naked flame or any incandescent material. Do not smoke. Do not empty into drains. Do not store near combustible materials. Take precautionary measures against static discharges. Prevent vapour buildup by providing adequate ventilation during and after use.

7.2 Conditions for safe storage, including any incompatibilities Do not store near combustible materials. Storage of flammable liquids

7.3 Specific end use(s) not determined

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1

Threshold lin	nits		
106-97-8	butan	800 ppm (8 h)	1000 ppm (15 min)
		1900 mg/m ³ (8 h)	2350 mg/m ³ (15 min)
74-98-6	propan	800 ppm (8 h)	1100 ppm (15 min)
		1500 mg/m ³ (8 h)	2000 mg/m ³ (15 min)
64742-49-0	Naphtha(petroleum),	500 ppm (8 h)	630 ppm (15 min)
	hydrotreatedlight	1800 mg/m ³ (8 h)	2300 mg/m ³ (15 min)

8.1.2 Other information on limit values There is no data available for this product. 8.1.3 Limit values in other countries

Limit values in other countries There is no data available for this product.

8.1.4 DNELS There is no data available for this product.
8.1.5 PNECS

There is no data available for this product.

8.2 Exposure controls

8.2.1 Appropriate engineering controls not determined

Date 17.8.2015

Previous date: 17.8.2015

8.2.2 8.2.2.1	Individual protection measures Respiratory protection Provide adequate ventilation. Do not inhale aerosol. Even in case of a full release, due to the small amount of substances present, it is not expected that exposure limits will be reached.
8.2.2.2	Hand protection It is good practice in industrial hygiene to avoid contact with solvents by using appropriate protective measures whenever possible.
8.2.2.3	Eye/face protection Avoid contact with the skin and the eyes.
8.2.2.4	Skin protection Avoid contact with the skin and the eyes.
8.2.3	Environmental exposure controls There is no data available for this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 9.1.1	Important Health Safety and Environmer Appearance aerosol	ntal Information
9.1.2	Odour	hydrocarbon-like
9.1.3	Odour threshold	not determined
9.1.4	рН	7
9.1.5	Melting point/freezing point	-10°C
9.1.6	Initial boiling point and boiling range	< -20 °C
9.1.7	Flash point	< 0 °C
9.1.8	Evaporation rate	not determined
9.1.9	Flammability (solid, gas)	Extremely flammable.
9.1.10	Explosive properties	
9.1.10.1	Lower explosion limit	2,3 til-%
9.1.10.2	Upper explosion limit	9,5 til-%
9.1.11	Vapour pressure	There is no data available for this product.
9.1.12	Vapour density	There is no data available for this product.
9.1.13	Relative density	There is no data available for this product.
9.1.14	Solubility(ies)	
9.1.14.1	Water solubility	insoluble
9.1.14.2	Fat solubility (solvent - oil to be specified)	Soluble in hydrocarbons
9.1.15	Partition coefficient: n-octanol/water	There is no data available for this product.
9.1.16	Auto-ignition temperature	There is no data available for this product.
9.1.17	Decomposition temperature	There is no data available for this product.
9.1.18	Viscosity	There is no data available for this product.
9.1.19	Explosive properties	There is no data available for this product.
9.1.20	Oxidising properties	There is no data available for this product.
9.2	Other information	

10. STABILITY AND REACTIVITY

Date 17.8.2015

 10.1 Reactivity Exposure to sunlight.
 10.2 Chemical stability Stable
 10.3 Possibility of hazardous reactions There is no data available for this product.

- 10.4 Conditions to avoid Do not expose to temperatures above 50 °C.
 10.5 Incompatible materials
 - No data is available on the product itself.
- **10.6 Hazardous decomposition products** No data is available on the product itself.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

No data is available on the product itself.

11.1.1 Acute toxicity LD50/oral/rat =>5840 mg/kg OECD Test Guideline 401 LC50/inhalation/ 4 h/rat =>23.3 mg/LOECDOECD Test Guideline 403 LD50/dermal/rat ==>2920 mg/kgOECD Test Guideline 402

11.1.2 Irritation and corrosion

Solvents may degrease the skin. Prolonged skin contact may cause skin irritation.

11.1.3 Sensitisation

No data is available on the product itself.

- **11.1.4 Subacute, subchronic and prolonged toxicity** No data is available on the product itself.
- **11.1.5 STOT-single exposure** Aspiration hazard
- **11.1.6 STOT-repeated exposure** Aspiration hazard
- **11.1.7 Aspiration hazard** Aspiration hazard if swallowed can enter lungs and cause damage.
- **11.1.8** Other information on acute toxicity No data is available on the product itself.

12. ECOLOGICAL INFORMATION

- 12.1 Toxicity
- 12.1.1 Aquatic toxicity
 - LC50/96h/rainbow trout =13.4mg/L (OECD 203)

Voi aiheuttaa pitkäaikaisia haittavaikutuksia vesiympäristössä.

12.2 Persistence and degradability

12.2.1 Biodegradation

There is no data available for this product.

12.2.2 Chemical degradation There is no data available for this product.

12.3 Bioaccumulative potential There is no data available for this product.

0/ =			
PRF Si	licon Oil .		
Date 17.	Date 17.8.2015 Previous date: 17.8.2015		
12.4	Mobility in soil There is no data available for this product.		
12.5	Results of PBT and vPvB assessment		
12.6	Other adverse effects		
13. D	ISPOSAL CONSIDERATIONS		
13.1	Waste treatment methods Do not burn, or use a cutting torch on, the empty drum. Dispose of in accordance with local regulations.		
13.2	Waste from residues / unused products There is no data available for this product.		

Page 6/6

14. TRANSPORT INFORMATION

SAFETY DATA SHEET

14.1	UN number	1950
14.2	UN proper shipping name	Aerosols
14.3	Transport hazard class(es)	2.1
14.4	Packing group	2
14.5	Environmental hazards	May cause long-term adverse effects in the aquatic environment.
146	Created procesutions for usars	

14.6 Special precautions for users

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

15. REGULATORY INFORMATION

- **15.1** Safety, health and environmental regulations/legislation specific for the substance or mixture 2B Aerosols
- 15.2 Chemical safety assessment

16. OTHER INFORMATION

16.1 Additions, Deletions, Revisions REGULATION (EC) No 453/2010

16.5 List of relevant R phrases, hazard statements, safety phrases and/or precautionary statements R12 Extremely flammable. P38 Irritating to skin

- R38 Irritating to skin.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.

16.8 Additional information available from:

tilaukset(at)taerosol.com