

Eaton PV-355ANH3

Catalog Number: PV-355ANH3

Fuse-link, high speed, 355 A, DC 1000 V, NH3, gPV, UL PV, UL, IEC, dual indicator

General specifications

Product Name	Catalog Number
Eaton Bussmann series photovoltaic fuses	PV-355ANH3
	Packing Unit
	Case Pack
	Pack
EAN	Quantity
5027590353465	12
5027590325998	3
Gross Weight	Length
12.336 kg	385 mm
3.296 kg	240 mm
Width	Height
280 mm	175 mm
152 mm	95 mm
Volume	ERP Name
18865 cm ³	SAP-UNITY
3465.6 cm ³	SAP-UNITY
Product Length/Depth	Product Height
80 mm	32 mm
Product Width	Product Weight
51 mm	1100 g
Compliances	Certifications
CE Marked	IEC 60269
RoHS Compliant	UL Listed
	CSA Certified

Electrical rating

Amperage Rating

355 A

Voltage rating

1000 Vdc

Interrupt rating

50 kAIC

Class

Class gPV

Pre arc (I2T)

44500

Watt losses

46 W

Product specifications

Application

Photovoltaic systems, inverters ,Photovoltaic array combiners and disconnects

Fuse type

PV-ANH3

Fuse indicator

Combination fuse status indicator

Fuse size

NH3

Fitted with:

Blade without bolt holes

Compatible fuse holder

Suitable for

SD3-D-PV NH Fuse base

Do pobrania

mCAD model

[PV_300-400A_NH3_STEP.stp](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. Wszelkie
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia