


Polyamid-Fitting 90



Material	PA 6.6
Schutzart	IP55
Dauergebrauchstemperatur	-30°C – +80°C
Lieferfarbe	schwarz (RAL 7031), grau (RAL 9005)

RoHS

- // rot
- // grau
- //



AG	d mm	D mm	CL mm	H mm	L mm	passend zu Polyamid-Schlauch DN	Best.-Nr. grau	Best.-Nr. schwarz
m12	8,2	18,7	11	36,3	35,7	6	1.535.1200.50	1.535.1201.50
m16	10,8	21,7	11	37,3	38,5	10	1.535.1600.51	1.535.1601.51
m16	10,9	26	11	41	43,8	12	1.535.1600.50	1.535.1601.50
m20	14,7	28	11	44	46	14	1.535.2000.51	1.535.2001.51
m20	15,2	32	13	51,5	51	17	1.535.2000.50	1.535.2001.50
m25	18,7	39,5	16	61,2	64,3	23	1.535.2500.50	1.535.2501.50
Pg 7	8,2	18,7	11	36,3	35,7	6	1.535.0700.14	1.535.0701.14
Pg 9	10,3	21,7	11	37,3	38,5	10	1.535.0900.14	1.535.0901.14
Pg 11	13,3	26	11	41	43,8	12	1.535.1100.14	1.535.1101.14
Pg 13,5	15,3	28	11	44	46	14	1.535.1300.14	1.535.1301.14
Pg 16	16,6	32	13	51,5	51	17	1.535.1600.14	1.535.1601.14
Pg 21	22,4	39,5	16	61,2	64,3	23	1.535.2100.14	1.535.2101.14