


Polyamid-Schlauch Slit



Material	Polyamid
Dauergebrauchstemperatur	-40 °C – +120 °C
Lieferfarbe	grau (RAL 7031), schwarz (RAL 9005)

RoHS

// Rohmaterial nach UL 94



Größe DN	d mm	D mm	R mm	Best.-Nr. grau	Best.-Nr. schwarz
6	6,5	10	15	1.527.0600.00	1.527.0601.00
10	10	13	25	1.527.0900.00	1.527.0901.00
12	12	15,8	35	1.527.1100.00	1.527.1101.00
14	14,2	18,4	35	1.527.1300.00	1.527.1301.00
17	16,5	21,2	40	1.527.1600.00	1.527.1601.00
23	23	28,4	45	1.527.2100.00	1.527.2101.00
29	29	34,5	55	1.527.2900.00	1.527.2901.00
37	36	42,5	65	1.527.3600.00	1.527.3601.00
50	48	54,5	80	1.527.4800.00	1.527.4801.00

Polyamid-Cut



Material Gehäuse aus Kunststoff / Metall, gummierter Griff

Lieferfarbe rot

// ermöglicht einen exakten, geraden und sicheren Schnitt von Polyamid-Wellrohren

Schneidbereich	passend zu DN	Best.-Nr.
0–26 mm	0–17	1.503.2600.00
0–63 mm	0–50	1.503.6300.00