

Product data

Product code	VC05-0215	STK-code	1912372	EAN-code	6410019123722
Product name	OTL-connector 1xAl/Cu 95-300mm ² (Yellow Green)			ETIM class	EC000897
Wires	1xAl/Cu 95-300 mm ²				

Technical data


Nominal current (IEC)	Cu	490	A
	Al	440	A
Nominal voltage (IEC)	1000 V AC / 1500 V DC		
		-	
		-	
		-	
Number of poles		1	pcs
Max. Cross section		300	mm ²
Tightening torque			
	95-150 mm ²	30	Nm
	185-300 mm ²	60	Nm
		-	
		-	
Min. installation temperature		+5	°C
Operating temperature		-25...+80	°C
Weight		212	g
IP-protection		IP20	
Standards	EN 61238-1; EN 60947-7-1		
Color / Material	Green RAL 6018, Yellow RAL 1016/ PA66-V0		
Mounting / Connection	DIN rail and screw (M5) mounting		



Description

OTL-connectors are designed for connecting and branching aluminium and copper conductors. The body is made of tin plated aluminium. Housing is made of UL94 V0 class polyamide.

Drawing



Package

Package	Box	Pcs / Package	3	Weight [kg]	0,69
Length [mm]	210	Width [mm]	155	Height [mm]	105

Ouneva Oy

Teollisuustie 21
FI-82730 Tuupovaara
Finland

Tel. +358 400 179 750
info@ouneva.fi

www.ounevagroup.fi
www.ounevaproducts.fi