


# RG-Coaxial Cables



Type	RG 174 A/U	RG 174 U	RG 178 B/U	RG 179 B/U	RG 180 B/U	RG 187 A/U
Part no.	40197	400189	40007	40008	40009	40010
<b>Cable structure</b>						
Inner conductor Ø mm	7 x 0,2 Steel/copper, bare	7 x 0,2 Steel/copper, bare	7 x 0,1 Steel/copper, silvered	7 x 0,1 Steel/copper, silvered	7 x 0,1 Steel/copper, silvered	7 x 0,1 Steel/copper, silvered
Insulation Ø mm	1,52 PE	1,52 PE	0,86 PTFE	1,6 PTFE	2,6 PTFE	1,6 PTFE
Outer conductor	Braid Tinned copper	Braid Tinned copper	Braid Silvered copper	Braid Silvered copper	Braid Silvered copper	Braid Silvered copper
Outer sheath	PVC	PVC	FEP	FEP	FEP	PFA
Min. bending radius app. mm	15	15	10	15	25	15
Temperature range °C	-35 to +80	-35 to +80	-55 to +200	-55 to +200	-55 to +200	-55 to +260
Copper weight kg/km	7,0	7,0	7,0	8,0	11,0	9,0
Outer Ø app. mm	2,8	2,6	1,8	2,5	3,7	2,6
Weight app. kg / km	11	11	8	16	28	17

<b>Electrical characteristics</b>						
Impedance (Ohm)	50 ± 2	50 ± 2	50 ± 2	75 ± 3	95 ± 5	75 ± 3
Frequency range						
f (max.) GHz	1	1	3	3	3	3
Propagation velocity v/c	0,7	0,7	0,7	0,7	0,7	0,7
Attenuation at 20°C (db/100m)						
100 MHz	30	30	43	28	20	28
200 MHz	45	45	62	41	33	41
500 MHz	73	73	102	69	-	69
800 MHz	93	93	134	92	-	92
1000 MHz	-	-	-	-	-	-
1350 MHz	-	-	-	-	-	-
1750 MHz	-	-	-	-	-	-
Capacitance pF/m	101	101	93	63	50	64
Rel. velocity of propagation %	70	70	70	70	70	70
Insulation resistance MΩ x kmmin.	10 <sup>5</sup>	10 <sup>5</sup>	10 <sup>5</sup>	10 <sup>5</sup>	10 <sup>5</sup>	10 <sup>5</sup>
Loop resistance max. (Ω/km)	360	360	860	840	840	840
Nominal peak voltage kVs	1	1	1	1	2	1
Dielectric strength 50 Hz kV eff	2	2	2	2	2	2

Dimensions and specifications may be changed without prior notice.

## Note

- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers.
- The colour at FEP and PFA outer sheath is brown or white as per production outlet.
- RG-Coaxial types are in accordance with US-Military specifications MIL-C-17.
- RG/U: R=Radio, G=Guide, U=Utility

## Application

Coaxial cables are used in high frequency transmission, especially for transmitters and receivers, computers, radio and TV transmissions. The varied mechanical, thermal and electronic properties of Coaxial cables mean that they can be used up into the GHz levels, as per cable type.