


DC/DC CONVERTER RV-16

24V / 12V (13.8V) 70W

	<table> <tr><td>Input voltage [VDC]:</td><td>15÷30</td></tr> <tr><td>Output voltage [VDC]:</td><td>13.8</td></tr> <tr><td>Power [W]:</td><td>70</td></tr> <tr><td>Maximum continuous current [A]:</td><td>1.5</td></tr> <tr><td>Overload protection [A]:</td><td>5</td></tr> <tr><td>Fail protection type [A]:</td><td>Fuse 5A</td></tr> <tr><td>Thermal protection:</td><td>80°C</td></tr> <tr><td>Overvoltage protection [V]:</td><td>NO</td></tr> <tr><td>Stand by current:</td><td>0mA</td></tr> <tr><td>Output voltage ripple:</td><td>0mV</td></tr> <tr><td>Input voltage ripple:</td><td>0mV</td></tr> <tr><td>Operating temperature range:</td><td>-25 ~ +55°C</td></tr> <tr><td>Galvanic isolation:</td><td>NO</td></tr> <tr><td>Efficiency:</td><td>-</td></tr> <tr><td>Cooling type:</td><td>Passive</td></tr> <tr><td>Connection:</td><td>Terminal block</td></tr> <tr><td>Housing:</td><td>Aluminium</td></tr> <tr><td>IP67 protection:</td><td>NO</td></tr> <tr><td>Dimensions LxWxH [mm]:</td><td>171x75x32</td></tr> <tr><td>Weight [g]:</td><td>400</td></tr> <tr><td>Safety:</td><td>EN 60950</td></tr> <tr><td>Emission:</td><td>EN 55014-1</td></tr> <tr><td>Immunity:</td><td>EN 55014-2</td></tr> <tr><td>Product code:</td><td>7016001</td></tr> </table>	Input voltage [VDC]:	15÷30	Output voltage [VDC]:	13.8	Power [W]:	70	Maximum continuous current [A]:	1.5	Overload protection [A]:	5	Fail protection type [A]:	Fuse 5A	Thermal protection:	80°C	Overvoltage protection [V]:	NO	Stand by current:	0mA	Output voltage ripple:	0mV	Input voltage ripple:	0mV	Operating temperature range:	-25 ~ +55°C	Galvanic isolation:	NO	Efficiency:	-	Cooling type:	Passive	Connection:	Terminal block	Housing:	Aluminium	IP67 protection:	NO	Dimensions LxWxH [mm]:	171x75x32	Weight [g]:	400	Safety:	EN 60950	Emission:	EN 55014-1	Immunity:	EN 55014-2	Product code:	7016001
Input voltage [VDC]:	15÷30																																																
Output voltage [VDC]:	13.8																																																
Power [W]:	70																																																
Maximum continuous current [A]:	1.5																																																
Overload protection [A]:	5																																																
Fail protection type [A]:	Fuse 5A																																																
Thermal protection:	80°C																																																
Overvoltage protection [V]:	NO																																																
Stand by current:	0mA																																																
Output voltage ripple:	0mV																																																
Input voltage ripple:	0mV																																																
Operating temperature range:	-25 ~ +55°C																																																
Galvanic isolation:	NO																																																
Efficiency:	-																																																
Cooling type:	Passive																																																
Connection:	Terminal block																																																
Housing:	Aluminium																																																
IP67 protection:	NO																																																
Dimensions LxWxH [mm]:	171x75x32																																																
Weight [g]:	400																																																
Safety:	EN 60950																																																
Emission:	EN 55014-1																																																
Immunity:	EN 55014-2																																																
Product code:	7016001																																																

- increasing voltage
- can be connected in parallel



ISO 9001



WWW.AZODIGITAL.COM
 SALES@AZODIGITAL.COM

MADE IN POLAND