

SKINDICHT® RWV-M

Strain relief
Sealed by incised sealing ring
Corrosion-resistant
Decrease in installation height
Seawater-resistant



Corrosion-resistant



Space requirement



Connector with standard housing unit



Temperature-resistant

Application range

Angled glands are used in areas where cables have to run in parallel to the housing wall.
Electric motor manufacturing
Machine and equipment manufacturing
Plant engineering
Light and sound applications

Product Make-up

Metric connection thread acc. to EN 50262

Note

Counter nut to be used: SKINDICHT® SM-M

Technical Data

Classification:

ETIM 5.0 Class-ID: EC000441
ETIM 5.0 Class-Description: cable screw gland

Material:

Body: zinc die-casting, nickel-plated
Compression screw and hexagon nut: nickel-plated brass
Incised sealing ring: CR/NBR
O-ring: NBR

Protection rating:

IP 55

Temperature range:

-20°C to +100°C

Note

Photographs are not to scale and do not represent detailed images of the respective products.



**SKINDICHT® RWV-M**

Part number	Article designation / size	Clamping range ØF (mm)	L	SW1	Ø A1	SW2	Ø A2	Ø G	Height (mm)	Overall length/ C (mm)	Thread length/ D (mm)	SW3	Pieces / PU
SKINDICHT® RWV-M													
52107800	12 x 1,5	5	20.5	14	16	12	13.2	8	5	26,1	11.5	17	25
52107810	16 x 1,5	9 - 3	23.5	18	20	16	17.6	12	5	28,6	11.5	22	25
52107820	20 x 1,5	13 - 4	28.5	22	24	20	22.2	15	5	35,1	12.5	27	25
52107830	25 x 1,5	17,5 - 8,5	31.0	27	29	25	27.5	20	5	38,1	13.5	32	10
52107840	32 x 1,5	25 - 16	33.0	34	36	32	35.2	27	5	44,6	13.5	41	10
52107850	40 x 1,5	32 - 23	43.0	42	45	40	43.5	35	5	53,1	15.5	46	5

SKINDICHT® RWV-M

