

# SD / VS / HT

## holder accessories



### SD / VS / HT

Fittings for system holder SH/SHV

### Material

Polyamide PA 6

- halogen-free

### Technical Data

Temperature range: -40°C to +110°C

### Properties

- Resistant to fuels, mineral oils, greases, weak bases, weak acids

#### SD cap for holder

Part No. grey	Part No. black	Suitable for tube ND mm	Unit	net EUR/100 items at acceptance of		
				up to 100	101 - 500	501 - 1000
94671	99278	7,5/10	100	o. r.	o. r.	o. r.
94672	99279	12	50	o. r.	o. r.	o. r.
94673	99280	14/16/17	50	o. r.	o. r.	o. r.
94674	99281	21/23	50	o. r.	o. r.	o. r.
94675	99282	29	30	o. r.	o. r.	o. r.
94676	99283	36/37	20	o. r.	o. r.	o. r.
94677	99284	48/50	20	o. r.	o. r.	o. r.

#### VS bond bridge for holder

Part No. grey	Part No. black	Suitable for tube ND mm	Unit	net EUR/100 items at acceptance of		
				up to 100	101 - 500	501 - 1000
94679	99286	alle	100	o. r.	o. r.	o. r.

#### HT hut-rail clip for holder

Part No. grey	Part No. black	Suitable for tube ND mm	Unit	net EUR/100 items at acceptance of		
				up to 100	101 - 500	501 - 1000
94678	99285	alle	50	o. r.	o. r.	o. r.

o. r. = on request