

SILVYN® AS-P

SILVYN® AS-P is a helically wound, one-hooked metal conduit with PVC jacket



SILVYN® MSK-M

SILVYN®
US/US-M + US-ED
IP 65

SILVYN® US-EDU-A6

SILVYN® US MS-DR



Waterproof



Robust



Mechanical resistance

Benefits

Protects against liquids
High-tensile
High crush-resistance
Flexible
High mechanical resistance

Application range

Mechanical engineering
Plant engineering
Automation technology
Used in areas where liquids are present
Applications with high mechanical stress

Norm references / Approvals

VDE
DIN 49012, complies with design I according to DIN EN IEC 61386-23
In EX-area according to EN 1127-1

SILVYN® AS-P**Product Make-up**

Helically-wound metal protective conduit with interlocked profile
PVC sheath

Technical Data

Classification:	ETIM 5.0 Class-ID: EC001179 ETIM 5.0 Class-Description: Protective metallic hose
Colour delivered:	Grey
Material:	Inner conduit: steel, galvanised Outer sheath: PVC
Temperature range:	-25°C to +80°C Short-term: up to +100°C

Note

Photographs are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

**SILVYN® AS-P**

Article number	Nominal size	ID x OD mm	Bending radius (mm)	Suitable for SILVYN® MSK-M	Suitable for SILVYN® US-M	Suitable for SILVYN® US
SILVYN® AS-P						
64400010	10	7 x 10	32	12 x 1,5	10 x 1,0	7
64400020	14	10 x 14	40	16 x 1,5	12 x 1,5	9
64400030	17	13 x 17	45	20 x 1,5	16 x 1,5	11
64400040	19	15 x 19	52	-	-	13,5
64400050	21	17 x 21	58	25 x 1,5	20 x 1,5	16
64400060	27	22 x 27	72	32 x 1,5	25 x 1,5	21
64400070	36	29 x 36	98	40 x 1,5	32 x 1,5	29
64400080	45	38 x 45	118	50 x 1,5	40 x 1,5	36
64400090	56	49 x 56	140	63 x 1,5	50 x 1,5	48
SILVYN® AS-P 10 M						
64400100	10	7 x 10	32	12 x 1,5	10 x 1,0	7
64400110	14	10 x 14	40	16 x 1,5	12 x 1,5	9
64400120	17	13 x 17	45	20 x 1,5	16 x 1,5	11
64400130	19	15 x 19	52	-	-	13,5
64400140	21	17 x 21	58	25 x 1,5	20 x 1,5	16
64400150	27	22 x 27	72	32 x 1,5	25 x 1,5	21
64400160	36	29 x 36	98	40 x 1,5	32 x 1,5	29
64400170	45	38 x 45	118	50 x 1,5	40 x 1,5	36
64400180	56	49 x 56	140	63 x 1,5	50 x 1,5	48

Last Update (11.07.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.deYou can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16