

SILVYN® US

SILVYN® US is a nickel-plated brass conduit insert for use with SILVYN® US-M or separately to cover sharp conduit endings



Temperature-resistant



Robust



Space requirement



Maximum vibration protection

Benefits

High tensile strength
Space-saving
Vibration protection
All-purpose

Application range

In combination with protective conduit:
SILVYN® AS/AS-P/EDU-AS/EMC AS-CU
SILVYN® FPS/FD-PU/FPS-EDU
Mechanical engineering
Plant engineering

Product features

Compact design

Product Make-up

PG connection thread
Hexagonal collar
Threaded sleeve
Sealing element
Cap nut

Last Update (18.07.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

SILVYN® US**Technical Data**

Classification:	ETIM 5.0 Class-ID: EC001180 ETIM 5.0 Class-Description: Screw connection for protective metallic hose
Material:	Body: nickel-plated brass Sealing ring: TPE
Protection rating:	IP 40 (with SILVYN® AS, EDU-AS and EMC AS-CU) IP 54 (with SILVYN® FPS, FD-PU, FPS-EDU) IP 65 (with SILVYN® AS-P)
Temperature range:	-40°C to +125°C

Note

Photographs are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

Article number	PG size	Clear opening (mm)	Suitable conduit nominal size
SILVYN® US for SILVYN® FPS / FD-PU			
55502651	7	6	10
55502652	9	9	14
55502653	11	11.5	17
55502654	13.5	13	19
55502655	16	14.5	21
55502656	21	19.5	27
55502657	29	26.5	36
55502658	36	36	45
55502659	48	45.5	56
SILVYN® US for SILVYN® AS			
55502661	7	6.5	10
55502662	9	10	14
55502663	11	12.5	17
55502664	13.5	14.5	19
55502665	16	16	21
55502666	21	21.5	27
55502667	29	29	36
55502668	36	38	45
55502669	48	49	56
SILVYN® US for SILVYN® AS-P			
55502671	7	6	10
55502672	9	8.5	14
55502673	11	11.5	17
55502674	13.5	13.5	19
55502675	16	15.5	21
55502676	21	20.5	27
55502677	29	27.5	36
55502678	36	36.5	45
55502679	48	47.5	56
SILVYN® US for SILVYN® EDU-AS / EMC AS-CU			
55502680	7	6	10
55502681	9	8.5	14
55502682	11	11.5	17
55502683	13.5	13.5	19

Last Update (18.07.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

 You can find the current technical data in the corresponding data sheet.
 PN 0456 / 02_03_16



Article number	PG size	Clear opening (mm)	Suitable conduit nominal size
55502684	16	15.5	21
55502685	21	20.5	27
55502686	29	27.5	36
55502687	36	36.5	45
55502688	48	47.5	56
SILVYN® US for SILVYN® FPS-EDU			
55502689	9	8.5	14
55502690	11	11	17
55502691	13.5	13	19
55502692	16	14.5	21
55502693	21	19.5	27
55502694	29	27.5	36
55502696	36	35.5	45
55502697	48	47	56

Last Update (18.07.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

SILVYN® US

