

## Isolating plugs - ST-K 4 - 5025462

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Isolating connector, can be used in UK...-TG, UKK...-TG, UDK...-TG, MBK...-TG, DIK...-TG, DOK...-TG, and ZFK...-TG disconnect terminal blocks, color: gray

### Key Commercial Data

|                                      |                                                                                                        |
|--------------------------------------|--------------------------------------------------------------------------------------------------------|
| Packing unit                         | 50 pc                                                                                                  |
| Minimum order quantity               | 50 pc                                                                                                  |
| GTIN                                 | <br>4 017918 095321 |
| Weight per Piece (excluding packing) | 1.6 g                                                                                                  |
| Custom tariff number                 | 85366990                                                                                               |
| Country of origin                    | Germany                                                                                                |

### Technical data

#### General

|                                        |      |
|----------------------------------------|------|
| Color                                  | gray |
| Insulating material                    | PA   |
| Flammability rating according to UL 94 | V2   |

#### Dimensions

|        |         |
|--------|---------|
| Width  | 4.5 mm  |
| Length | 10 mm   |
| Height | 31.2 mm |

#### General

|                       |       |
|-----------------------|-------|
| Nominal current $I_N$ | 16 A  |
| Nominal voltage $U_N$ | 400 V |
| Number of positions   | 1     |

#### Connection data

|                   |                 |
|-------------------|-----------------|
| Connection method | Plug connection |
|-------------------|-----------------|

#### Standards and Regulations

|                                        |    |
|----------------------------------------|----|
| Flammability rating according to UL 94 | V2 |
|----------------------------------------|----|

## Isolating plugs - ST-K 4 - 5025462

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141199 |
| eCl@ss 4.1 | 27141199 |
| eCl@ss 5.0 | 27141145 |
| eCl@ss 5.1 | 27141145 |
| eCl@ss 6.0 | 27141149 |
| eCl@ss 7.0 | 27141149 |
| eCl@ss 8.0 | 27141140 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000897 |
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC002497 |
| ETIM 5.0 | EC000489 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11     | 39121409 |
| UNSPSC 12.01  | 39121409 |
| UNSPSC 13.2   | 39121409 |

### Approvals

#### Approvals

Approvals

EAC / EAC

Ex Approvals

Approvals submitted

#### Approval details

|     |
|-----|
| EAC |
|-----|

|     |
|-----|
| EAC |
|-----|

## Isolating plugs - ST-K 4 - 5025462

### Accessories

Accessories

Documentation

Mounting material - ST-IL - 3039900

Operating decal for the ST terminal block



---

### Universal tools

Plug extraction tool - TZ - 0306704



Connector pliers, simplify removing the isolating connector from a closed row of terminal blocks (if installed individually)