

S-VHS Video cable



Applications:
Flexible cable with separately shielded and insulated cores for assembled cables. Suitable to connect Mini-DIN 4 poles S-VHS plug.

Characteristics:
 Conductors: O.F.C. tinned copper
 Cond. Insulation: PVC
 Core colours: Yellow, Grey
 Shields: Spiral covering 100% O.F.C. tinned copper
 PVC
 Inner Sheaths: PVC
 Inner Sheath colours: White, Red
 External Sheath: PVC
 Sheath colour: Black



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C200	2	2 x 0,08 (28 AWG)	12x0,10	1,0	2,0	4,6	100	B	3,0

nightly blue®



S-VHS Video & Audio cable



Firestop®

Applications:
Special flat cable with separately shielded and insulated cores for assembled cables. Flat cable composed of: 1 S-VHS and 2 Audio cables. Suitable to connect n° 1 Mini-DIN 4 poles S-VHS plug and n° 2 RCA audio plugs.

Characteristics:
S-VHS
 Conductors: O.F.C. tinned copper
 Cond. Insulation: PVC
 Core colours: Yellow, Grey
 Shields: Spiral covering 100% O.F.C. tinned copper
 PVC
 Inner Sheaths: PVC
 Inner Sheath colours: White, Red
Audio
 Conductors: O.F.C. red copper
 Cond. Insulation: Compact PE
 Core colours: Red, White
 Shields: Spiral covering 100% O.F.C. red copper
 External Sheath: Flame Retardant PVC CEI 20-22/II°
 Sheath colour: Blue-night



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Dimension mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C142	2	2 x 0,08 (28 AWG)	12x0,10	1,0	2,0	5,0 x 14,5	100	B	9,5
	+2	+2 x 0,25 (23 AWG)	8x0,20	2,3					

Conductor Resistance	Capacity Core/core	Capacity Core/shield
Ω/Km ± 5%	pF/mt	pF/mt
210	65	230
75	36	96
	Max rated Voltage AC - V	Operative Temperature °C
	49	-15 / +70