



Applications:
Professional and extra-flexible digital audio cable 110 Ω AES/EBU for DMX or sound transmission in recording studios and conference rooms.

Characteristics:
 Conductors: O.F.C. silver plated copper
 Cond. Insulation: PPE
 Core colours: Red, Blue
 Waste filler between conductors
 Total taping in unweaved polyester
 Drain wire: O.F.C. tinned copper
 Shield: Braided covering 95%
 O.F.C. silver plated copper
 Sheath: PVC
 Sheath colour: Silver



tasker® Code	Cond. number	Nominal section mm. AWG	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C850	2	2 x 24 (0,22 mm ²)	11x0,16	1,5	6,0	100	B	6,0

Conductors and shield in Silver-plated copper

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
90	50	95
Impedance Ω	Max rated Voltage AC - V	Operative Temperature °C
110	49	-15 / +70

Digital audio cables – DMX 110 Ω



Applications:
Professional digital audio cables 110 Ω AES/EBU for DMX and audio installations on long distances in big spaces as for example airports, megastores, public buildings.

Characteristics:
 Conductors: O.F.C. tinned copper
 Cond. Insulation: PPE
 Core colours: Red, Blue
 Waste filler between conductors
 Total taping in unweaved polyester
 Drain wire: O.F.C. tinned copper
 Shield: Braided covering 85%
 O.F.C. tinned copper
 Sheath: Flame Retardant
 PVC CEI 20-22/II*
 Sheath colour: Blue-night



tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
TSK 1038	2	2 x 0,35 (22 AWG)	11x0,20	1,6	6,3	100	B	5,0
TSK 1039		2 x 0,50 (20 AWG)	16x0,20	2,0	6,6	100	B	
TSK 1040		2 x 0,75 (18 AWG)	24x0,20	2,3	7,4	100	B	

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
60	45	90
45	45	90
32	45	90
Impedance Ω	Max rated Voltage AC - V	Operative Temperature °C
110	49	-15 / +70