MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918

Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

Timer Relay click





PID: MIKROE-5562

Timer Relay Click is a compact add-on board that allows you to control the load with a timer. This board features the NE5555, a precision timer from <u>Diodes Incorporated</u>. It is a precision timing circuit capable of producing accurate time delays in a monostable mode of operation. The Timer Relay Click features the SRD-5VDC-SL-C, a relay from Ningbo, to control the connected load over the screw terminal. This Click board ™ makes the perfect solution for developing and controlling high-power applications that require delayed timing.

Timer Relay Click is supported by a $\underline{\mathsf{mikroSDK}}$ compliant library, which includes functions that simplify software development. This $\underline{\mathsf{Click}}$ board $\underline{\mathsf{mikroSDK}}$ comes as a fully tested product, ready to be used on a system equipped with the $\underline{\mathsf{mikroBUS}}^{\mathsf{m}}$ socket.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.





health and safety management system.



MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

Specifications

Туре	Relay
Applications	Can be used for developing and controlling high-power applications that require delayed timing
On-board modules	NE5555 - precision timer from Diodes Incorporated
Key Features	Time-delayed operation, trigger control by the host MCU or over the button, digital potentiometer for setting the threshold, screw terminals for connecting the load, long mechanical life of the relay, and more
Interface	SPI
ClickID	Yes
Compatibility	mikroBUS
Click board size	L (57.15 x 25.4 mm)
Input Voltage	3.3V or 5V

Resources

<u>mikroBUS™</u>

mikroSDK

Click board™ Catalog

Click Boards™

Downloads

Timer Relay click schematic

Timer Relay click 2D and 3D files

NE555 datasheet

SRD-5VDC-SL-C datasheet

TPL0501 datasheet

Timer Relay click example on Libstock

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.





health and safety management system.