



Fuses for Semiconductor Protection
Knife Blade Contact – German Standard

Size 000	Rated Voltage AC 500 V	Combi Indicator	Standard DIN 43620
---------------------------	---	------------------------	-------------------------------------

Rated Current [A]	Part No.	UL Rec.	Class	Weight [kg/1]	Pack
6	20 000 04.6		gR	0.11	3
10	20 000 04.10		gR	0.11	3
16	20 000 04.16		gR	0.11	3
20	20 000 04.20		gR	0.11	3
25	20 000 04.25		gR	0.11	3
32	20 000 04.32		gR	0.11	3
40	20 000 04.40		gR	0.11	3
50	20 000 04.50		gR	0.11	3
63	20 000 04.63		gR	0.11	3
80	20 000 04.80		gR	0.11	3

Size 00	Rated Voltage AC 500 V	Combi Indicator	Standard DIN 43620
--------------------------	---	------------------------	-------------------------------------

Rated Current [A]	Part No.	UL Rec.	Class	Weight [kg/1]	Pack
100	20 001 04.100		gR	0.15	3
125	20 001 04.125		aR	0.15	3
160	20 001 04.160		aR	0.15	3

Size 000 20 000 04	Size 00 20 001 04
A_{max} 2.13" (54 mm)	A_{max} 2.13" (54 mm)
B 0.60" (15 mm)	B 0.60" (15 mm)
C 1.85" (47 mm)	C 1.85" (47 mm)
D 0.80" (20.5 mm)	D 1.16" (29.5 mm)
E 1.60" (40.5 mm)	E 1.80" (46 mm)
F 0.24" (6 mm)	F 0.24" (6 mm)
G 1.38" (35 mm)	G 1.38" (35 mm)
H 2.05" (52 mm)	H 2.28" (58 mm)
I 0.28" (7 mm)	I 0.50" (13 mm)
L 3.07" (78 mm)	L 3.07" (78 mm)

