Product data sheet Characteristics

XALE3

Empty control station, Harmony XALE, plastic, light grey, 3 cut outs, for Harmony XB7





Main

Harmony XALE
Empty control station
XALE
For XB7 Ø 22 mm control and signalling units
3 cut-outs
Light grey (RAL 7035)
Light grey (RAL 7035)
ABS (acrylonitrile butadiene-styrene)
2 knock-outs, clamping capacity: 20 mm 6 knock-outs for ISO M20
5
IP54 conforming to IEC 60529

Complementary

Assembly style	For customer assembly
Product weight	0.1 Kg
Marking	CE

Environment

Protective treatment	TC
Ambient air temperature for storage	-4070 °C
Ambient air temperature for operation	-2555 °C
Electrical shock protection class	Class II conforming to IEC 60536
IK degree of protection	IK05 conforming to EN 50102
Standards	EN/IEC 62208 EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-5

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	9.500 Cm	
Package 1 Width	7.500 Cm	
Package 1 Length	15.000 Cm	
Package 1 Weight	94.000 G	

Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	8.300 Cm
Package 2 Width	12.200 Cm
Package 2 Length	33.400 Cm
Package 2 Weight	549.000 G
Unit Type of Package 3	S03
Number of Units in Package 3	30
Package 3 Height	30 Cm
Package 3 Width	30 Cm
Package 3 Length	40 Cm
Package 3 Weight	3.677 Kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information

Contractual warranty

Warranty 18 months

Product Life Status : Commercialised

